

Maperubber Black 25

Granulated Rubber Filler for Polyurethane Resin Underlayments, for Leveling Internal and External Ship Decks

FOR PROFESSIONAL USE ONLY

WHERE TO USE

Maperubber Black 25 is used as a filler material in polyurethane resin underlayments such as **Mapedeck® Flexiscreed** and **Mapedeck Litescreed**.

TECHNICAL CHARACTERISTICS

Maperubber Black 25 consists of rubber granules measuring a maximum of 2.5 mm in size and is ideally suited as a filler for polyurethane underlayments.

LIMITATIONS

- Do not use under any circumstances if the product is wet or damp.
- Avoid contact with oils and organic solvents.

HOW TO USE

Add **Maperubber Black 25** to a resin underlayment after mixing both of the underlayment's components with a power mixer.

COVERAGE/CONSUMPTION

Maperubber Black 25 is added to the underlayment mix at a dosage of up to approximately 40% by weight of the mixed resin.

PACKAGING

Bag: 44.1 lbs. (20 kg)

STORAGE

Store **Maperubber Black 25** in its original packaging in a cool, dry area and away from direct UV exposure. Do not use **Maperubber Black 25** if it becomes damp or wet.

Technical Data

PRODUCT INFORMATION	
Color	Black
Consistency	Granules
Particle size distribution	0.8 to 2.5 mm
Density	1.1 g/cm ³
Bulk density	0.5 g/cm ³ (average value)

ADDITIONAL INFORMATION

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:

Flooring: 1-800-992-6273

Concrete and heavy construction: 1-888-365-0614

Canada:

1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: December 9, 2025 MK 09894 (25-2340)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.
All Rights Reserved. © 2025 MAPEI Corporation.

