

Maperubber EPDM 15

Granulated Decorative EPDM filler for Aliphatic Polyurethane Self-Leveling Compounds

WHERE TO USE

Maperubber EPDM 15 is used as a decorative filler material for **Mapedeck Design** and **Mapedeck Soft Design** aliphatic polyurethane self-leveling compounds.

TECHNICAL CHARACTERISTICS

Maperubber EPDM 15 is easy to use and offered in a wide range of colors that is ideal for achieving the desired aesthetic effect.

RECOMMENDATIONS

- Never use if the product is wet or damp.
- Avoid product contact with organic oils and solvents.

APPLICATION PROCEDURE

Maperubber EPDM 15 is added to **Mapedeck Design** and **Mapedeck Soft Design** after the second part of the mixing process. After application of **Mapedeck Design** or **Mapedeck Soft Design**, broadcast the surface with **Maperubber EPDM 15** in the quantity required to achieve the desired appearance. Adding excessive **Maperubber EPDM 15** in the mixing or broadcast process can result in an undesirable appearance or failure of the finished surface.

COVERAGE/CONSUMPTION

Add to the resin at a suitable dosage to achieve the desired aesthetic effect. Excessive dosage may compromise the homogeneity of the aesthetic effect.

PACKAGING

55.1-lb. (25-kg) bags

STORAGE

Store the product in its original packaging in a dry area and away from direct UV exposure. Do not use *Maperubber EPDM 15* if it becomes damp or wet.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

Technical Data

Product Information	
Color	21 colors available
Consistency	Granules
Particle size distribution	0.5 to 1.5 mm
Density	1.59 g/cm ³
Bulk density	0.65 g/cm ³ (average value)

ADDITIONAL INFORMATION

Refer to the Safety Data Sheet (SDS) for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: January 27, 2026 MK 09895 (25-1688)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.
All Rights Reserved. © 2026 MAPEI Corporation.

