

UltraCare Marine Wax Remover

Multi-Action, Non-Rinse Detergent for Removing Metallic Wax

WHERE TO USE

UltraCare® Marine Wax Remover is recommended for removing coats of old metallic wax from resin surfaces, including double-curing wax. It may also be used for deep cleaning, and to remove wax from vinyl, linoleum and rubber flooring.*

** MAPEI recommends testing a small, inconspicuous area for color change prior to proceeding with product usage.*

TECHNICAL CHARACTERISTICS

UltraCare Marine Wax Remover is a multi-action, fast-acting detergent for removing wax and all types of metallic wax. It is a low-foaming formula that also works well for deep cleaning.

UltraCare Marine Wax Remover is a powerful, non-rinse detergent for removing wax from surfaces without the rinsing process normally required with other traditional products. Its deep cleaning action quickly emulsifies wax, metallic wax, dirt and other residues.

USE OF PRODUCT

UltraCare Marine Wax Remover effectively cleans surfaces using hand tools or by machine.

For removal of metallic wax, use a 10% concentration to cleaning water (1 L of product per 10 L of water). It is recommended to use **UltraCare Marine Wax Remover** with hot water for increased effectiveness.

For removal of double-curing metallic wax, use at a concentration of 15% to cleaning water (1.5 L of product per 10 L of water). It is recommended to use **UltraCare Marine Wax Remover** with hot water for increased effectiveness.

MAPEI recommends using a wet/dry vacuum cleaner to remove the cleaning solution from the floor surface after the cleaning process. No rinsing is required.

When the floor has dried, it will be ready for use, or for the next finishing operation such as application of a wax or sealer.

PACKAGING

1.32 U.S. gals. (5 L) jerrycan

STORAGE

Store *UltraCare Marine Wax Remove* in its original packaging in a dry place at a temperature of 32°F to 95°F (0°C to 35°C). The shelf life is 24 months in the original, sealed packaging. Protect from freezing weather.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

Technical Data

Product Information	
Consistency	Liquid
Color	Clear, fluorescent yellow
Density	0.96 g/cm ³ ± 0.01
Odor	Characteristic odor
Chemical characteristics	< 5% non-ionic surfactants, perfume, limonene and hexyl cinnamal
pH	12
Solubility in water	Fully soluble at all concentration levels
EC N. 648/2004 regulations	Complies

ADDITIONAL INFORMATION

Refer to the Safety Data Sheet (SDS) for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: March 9, 2026 MK 09936 (25-3312)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.
All Rights Reserved. © 2026 MAPEI Corporation.

