

CERFIX PROTRIM / PROTRIM IP / CERFIX PROTRIM N

External Corner Profiles



DESCRIPTION

Protrim is a versatile line of profiles designed to seal and protect external corners in ceramic tile flooring, providing a symmetrical and injury-proof finish that hides the 45-degree tile cuts. Available in various sizes, materials and finishes, **Protrim** profiles serve both decorative and functional purposes and complement profiles in the **Prolist** line, allowing for striking combinations and contrasts with different floor coverings.

In addition to sealing corners, **Protrim** profiles are suitable for sealing and protecting floors, stair edges, work surfaces and surfaces. However, it is important to note that polished and coated aluminum as well as PVC models are not recommended for floor use. Similarly, chrome-plated brass models are not suitable for floor installation or areas with heavy foot traffic.

Special components are offered for creating internal/external angles and end pieces, ensuring a harmonious and linear appearance. The **Protrim** range also includes a Flex version, crafted from anodized silver and natural brass, and designed for shaping via bending machines to match curved joint edges.

Note that titanium anodized aluminum models are not recommended for outdoor use.

MATERIALS

Anodized aluminum

These Al-Mg-Si profiles, heat-treated to T6 (6060 T6), are produced through extrusion and then anodized with a thickness of at least 15 µm. The external surface must be protected from scratches and rubbing. The profiles are highly resistant to chemical and atmospheric agents. However, it is important to note that when exposed to wet cement and its derivatives, they can produce alkaline substances that, if left untreated on the surface, may corrode the metal and lead to the formation of aluminum hydroxide. Therefore, it is essential to delicately and thoroughly clean the visible surface of the profile from cements, mortars/adhesives, cleaners, caulks and other materials.

It is worth mentioning that continuous wear, especially when these profiles are used on flooring, can cause the anodized surfaces to wear down over time, resulting in the loss of their original finish. Regular maintenance and care are recommended to preserve the quality and appearance of the profiles. See the “Care and Maintenance” section below.

Polished aluminum

These Al-Mg-Si alloy profiles, heat-treated to T6 temper (6463 T6), are manufactured through extrusion and subsequent mechanical treatment. They offer fair resistance to chemical agents. However, it is crucial to clean the visible surface of the profiles thoroughly from cements, mortars/adhesives, cleaners, caulks and other materials to prevent potential corrosion caused by alkaline substances from wet cement and its derivatives.

Furthermore, note that profiles made of polished aluminum are not suitable for use on floors and outdoors due to the risk of corrosion from alkaline substances.

Coated aluminum

These Al-Mg-Si alloy profiles, heat-treated to T6 temper (6060 T6), are produced through extrusion and then color-coated. While they offer a fair level of resistance to chemical and atmospheric agents, they are not suitable for handling mechanical stress, as this can damage the coated surface. Therefore, it is not recommended to use these profiles for flooring applications.

It is crucial to promptly clean the visible surface of the profile from cement, mortars/adhesives, cleaners, caulks and other materials to maintain the integrity of the varnish coating and prevent potential damage or corrosion.

Antibacterial coated aluminum

These Al-Mg-Si alloy profiles, heat-treated to T6 temper (6060 T6), are manufactured through extrusion and subsequently coated with antibacterial technology. This technology allows for a reduction of up to 99% of the most dangerous bacteria, and it is certified according to the strict international test JIS Z 2801: 2000.

While these profiles offer fair resistance to chemical and atmospheric agents, they are not suitable for handling mechanical stress, which can damage the coated surface. Therefore, it is not recommended to use these profiles for flooring applications.

It is important to promptly clean the visible surface of the profile from cement, mortars/adhesives, cleaners, caulks and other materials to maintain the integrity of the antibacterial varnish coating and prevent potential damage or corrosion.

Stainless steel

AISI 304 stainless-steel profiles feature substantial resistance to the principal chemical and atmospheric agents, lime, mortar and cleaning agents. They are recommended for use in more demanding environments such as the food industry, hospitals, pools and general exterior installations.

AISI 316 stainless-steel profiles feature substantial resistance to the principal chemical and atmospheric agents, lime and mortar and cleaning agents. Moreover, they afford good resistance to chlorine and saltiness, and are particularly well suited for extreme environments.

Natural brass

These CW624N alloy profiles are manufactured through extrusion. They exhibit good resistance to chemical agents and mechanical stress. They exhibit excellent resistance to chemical agents and mechanical stress. However, when brass is used on the visible surface side, it is prone to oxidation, resulting in a surface patina. In environments with strong atmospheric humidity or corrosive agents, brass can experience accelerated oxidation, leading to surface stains and spots.

When needed, the original natural appearance of the brass surface can be restored by using abrasives or specific polishing products.

Chrome brass

These CW624N alloy profiles are manufactured by extrusion and subsequently coated with chrome. They are resistant to UV rays, chemical and atmospheric agents, and should not be used on floors in areas subject to heavy foot traffic.

Rigid PVC

These profiles are made of rigid PVC vinyl that is lead-free, shock-resistant and self-extinguishing. The compound is stabilized using an eco-compatible salt-based Ca-Zn stabilizer.

Co-extruded rigid/plasticized PVC

These profiles are made of a rigid PVC compound that is lead-free, shock-proof, self-extinguishing and stabilized using an eco-compatible salt-based Ca-Zn stabilizer. The plasticized PVC compound component is lead-free, self-extinguishing and stabilized using an eco-compatible salt-based Ca-Zn stabilizer.

General note on metals

Aluminum, AISI 304 stainless steel and AISI 316 stainless steel are not resistant to all chemical compounds, particularly aggressive ones like hydrochloric acid (HCl) and phosphoric acid (H₃PO₄). Cleaning products such as muriatic acid, ammonia, bleach and sodium hypochlorite – commonly used for cleaning natural-stone,

ceramic and porcelain tiles – can damage the surface of these metals and may lead to intense corrosive reactions.

It is crucial to promptly and gently remove residues of cement, mortars/adhesives, cleaners, caulks and other materials from the surface of profiles to prevent damage. Additionally, if adhesive tape is used to mask the profiles, it should be removed within 1 hour to avoid any adverse effects.

PRODUCT INSTALLATION

Use the following steps to install a profile with mortar.

1. Remove the profile from the packaging and check that the thickness of the material you are installing matches the height of the selected profile (refer to the label).
2. Remove any protective or thermo-shrink film covering the finish of the profile, if present.
3. Determine the necessary length and cut the profile to the required measurement using appropriate tools.
4. Use a proper trowel to spread the mortar and get proper coverage.
5. Press and embed the profile onto the mortar so that it comes out from the holes on the side wing.
6. Carefully place and press the flooring, ensuring it aligns with the profile and maintains the proper distance for the gap (usually 1/32" to 5/64", or 1 to 2 mm).
7. Fill the gap between the flooring and the profile using the appropriate grout.
8. Clean any excess gap material, mortar/adhesive, detergent, etc., with a soft sponge and water within 10 minutes of application.

CARE AND MAINTENANCE

The care and maintenance of the materials used in the production of these profiles are closely tied to the type of alloy and finishing used. The following instructions outline the procedures for restoring the profile's original appearance as much as possible. These guidelines are intended to serve as general recommendations for cleaning, but they should be checked and applied on a case-by-case basis. It is important to note that there are specific responsibilities and guidelines for each stage of the product's life, starting from its installation.

Aluminum

These profiles require minimal maintenance and can be easily maintained using colorless alcohol diluted in water or regular detergents, excluding acid-based products such as hydrochloric or hydrofluoric acid. Various commercial brands offer a wide range of detergents, generally classified into three types:

- Alkaline type
- Neutral type
- Acid type

For cleaning purposes, it is recommended to use a neutral detergent diluted in water and rinse with water only, using a sponge or non-abrasive cloth to avoid scratches or damage to the anodization, shine or varnish. During cleaning, the following precautions should be taken:

- Avoid using acid or alkaline detergents as they can damage aluminum.
- Avoid abrasive products or materials.

- Do not use organic solvents on painted surfaces.
- Do not use detergents with unknown chemical compositions.
- Do not apply detergents directly to the surface.
- Clean surfaces at a relatively low temperature (maximum temperature of 86°F or 30°C) and away from direct sunlight.
- Use cold detergents (maximum temperature of 86°F or 30°C) and avoid spraying it on the surface.

After cleaning, always rinse the treated area with water and dry immediately with a soft cloth or rag. Regular maintenance with polishing products is unnecessary.

Ensure quick and precise cleaning of the profile following the instructions on the product's packaging to prevent the accumulation of cement deposits, caulk or similar substances that could damage the surface layers.

Stainless steel

Stainless-steel surfaces can be polished using suitable products that are readily available in stores. Stainless steel is easy to clean and highly hygienic, thanks to its smooth and nonporous surface that makes it difficult for the adherence and survival of bacteria and other microorganisms. Basic guidelines are sufficient to keep stainless-steel surfaces well maintained: Washing with hot water and soap, followed by thorough rinsing and drying with a soft cloth.

For surfaces exposed to atmospheric or aggressive agents, periodic cleaning is recommended to maintain the stainless steel's appearance and prevent corrosion. When cleaning brushed finish surfaces, always follow the direction of the grain and avoid cleaning across it. For scratches, use a detergent or polish specifically designed for stainless steel and a soft cloth. Avoid using detergents containing hydrochloric acid (muriatic acid), hydrofluoric acid or bleach, and refrain from prolonged contact with common steel objects or tools that may transfer ferrous particles (contamination) and cause rust stains on the stainless-steel surface. Also avoid direct contact with detergents containing chlorides unless the contact is brief and the surface is thoroughly rinsed afterward.

Additionally, prevent humid materials or sponges from remaining in contact with the stainless-steel surface for extended periods to avoid water stains.

Brass

These profiles require minimal maintenance and can be easily maintained using alcohol diluted in water or regular detergents, excluding acid-based products. For cleaning, it is recommended to use a neutral detergent diluted in water along with a rinsing agent of water only, using a sponge or nonabrasive cloth to prevent scratches or damage to the surface.

For maintenance purposes, a normal polishing product should be used.

PVC

These profiles require no specific maintenance and can be easily cared for using colorless water-diluted alcohol or water-diluted normal detergents (excluding acid-based or alkaline-based detergents). After


cleaning, rinse thoroughly with water only and use a sponge or nonabrasive cloth to prevent scratches or damage to the surface.

FIRE-CONTROL MEASURES

In case of fire, extinguish with fire-fighting chemical products, dry sand or solid fire-extinguishing agents.

NOTE

MAPEI profiles should be handled with care, and it is important to use suitable gloves to prevent cuts or injuries to the hands. The instructions provided here are based on our own experience and are for informational purposes only. It is crucial to confirm these instructions through practical experience. MAPEI will not be held responsible for any personal injury or material damage resulting from improper use of the product. The user is responsible for determining if the product is suitable for the intended task and must also assume responsibility for any incorrect installation of the material.



IPA/
IPB/
IPV/

CERFIX PROTRIM IP


Length = 8'10" or 2.7 m (20 pieces per package)		H				
Item	Finish		3/16" (4.5 mm)	5/16" (8 mm)	7/16" (11 mm)	9/16" (15 mm)
ALUMINUM						
IPA/	Silver anodized		95006	95178	95181	95185
	\$/pc					
IPB/	Bright polished silver		95008	–	–	–
	\$/pc					

Individually packaged

TREND
COLOR

CERFIX PROTRIM IP – TREND COLOR STONE

length = 8'10" or 2.7 m (20 pieces per package)		H			
Item	Finish	7/16" (11 mm)			
COLOR-COATED ALUMINUM					
IPV/	TREND COLOR STONE				
	Dark brown				95182
	Anthracite gray				95183
	Ancient gray				95184
	Grey				95186
	Rust				95187
	Bronze				95188
	Stone				95189
	Greige				95190
	Sand				95191
	Beige				95192
	White stone				95193
	Black stone				95194
\$/pc					





IPI/

CERFIX PROTRIM IP

Length = 8'10" or 2.7 m (20 pieces per package)		H				
Item	Finish		9/32" (7 mm)	5/16" (8 mm)	7/16" (11 mm)	1/2" (12.5 mm)
STAINLESS STEEL						
IPI/	Stainless steel AISI 304		95169	95170	95173	95174
	\$/pc					

Individually packaged



CERFIX PROTRIM

Length = 8'10" or 2.7 m
(20 pieces per package)

		H								
Item	Finish		1/8" (3 mm)	3/16" (4.5 mm)	1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	7/16" (11 mm)	1/2" (12.5 mm)	9/16" (15 mm)
ALUMINUM										
RA/	Silver anodized		92055	92056	92070	92072	92074	92060	92076	92078
	Gold anodized		92025	92026	92040	92042	92044	–	92046	–
	Titanium anodized		92085	92086	92087	92090	92094	–	92096	–
	\$/pc									
RB/	Bright polished silver		92315	92316	92310	92312	92314	92061	92318	–
	\$/pc									
RB/	Bright polished gold		92325	92326	92340	92342	92344	–	92348	–
RT/	Bright polished titanium		92015	92016	92018	92020	92022	–	92023	–
	\$/pc									
RAS/	Bright satin silver		92050	92051	92071	92073	92075	92062	92077	–
	Bright satin gold		–	–	92041	92043	92045	–	92047	–
RTM/	Bright satin titanium		92053	92057	92064	92066	92068	–	92079	–
	\$/pc									
COLOR-COATED ALUMINUM										
RV/	Matte white RAL 9003		–	–	–	92107	92108	92109	92110	–
	White RAL 9003		–	–	92100	92102	92104	92111	92106	–
	\$/pc									
ANTIBACTERIAL COLOR-COATED ALUMINUM										
RVH/	White RAL 9003		–	–	–	92112	92114	–	92116	–
	\$/pc									

Individually packaged



TA/ silver anodized aluminum

CERFIX PROTRIM – OUTSIDE CORNER

5 pieces per package

Item	Finish		1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	7/16" (11 mm)	1/2" (12.5 mm)
ALUMINUM							
TA/	Silver anodized		92606	92608	92610	92600	92612
	Gold anodized		92614	92616	92618	–	92619
	Titanium anodized		92564	92566	92568	–	92569
	\$/pc						
TB/	Bright polished silver		92690	92692	92694	92601	92696
	Bright polished gold		92700	92702	92704	–	92706
TAT/	Bright polished titanium		92724	92726	92728	–	92729
\$/pc							
TAS/	Bright satin silver		92710	92711	92712	92602	92713
	Bright satin gold		92720	92721	92722	–	92723
TATM/	Bright satin titanium		92714	92716	92718	–	92773
\$/pc							
COLOR-COATED ALUMINUM							
TV/	Matte white RAL 9003		–	92636	92637	92638	92639
	White RAL 9003		92620	92622	92624	92628	92626
	\$/pc						

No partial packaging




TIA/ silver anodized aluminum

CERFIX PROTRIM – INSIDE CORNER

5 pieces per package

Item	Finish		1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	7/16" (11 mm)	1/2" (12.5 mm)
ALUMINUM							
TIA/	Silver anodized		92570	92571	92572	92603	92573
	Gold anodized		92575	92576	92577	–	92578
	Titanium anodized		92554	92555	92556	–	92558
	\$/pc						
TIB/	Bright polished silver		92580	92581	92582	92604	92583
	Bright polished gold		92585	92586	92587	–	92588
TIAT/	Bright polished titanium		92730	92732	92734	–	92736
\$/pc							
TIAS/	Bright satin silver		92550	92551	92552	92605	92553
	Bright satin gold		92560	92561	92562	–	92563
	\$/pc						
COLOR-COATED ALUMINUM							
TIV/	Matte white RAL 9003		–	92646	92647	92648	92649
	White RAL 9003		92621	92623	92625	92629	92627
	\$/pc						

No partial packaging

**CERFIX PROTRIM**

Length = 8'10" or 2.7 m
(20 pieces per package)

		H			
Item	Finish		5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)
ALUMINUM					
RA/	Black anodized		92059	92063	92083
	\$/pc				
TREND COLOR STONE					
RV/	Dark brown		92135	92255	92369
	Ancient gray		92136	92256	92370
	Gray		92137	92257	92371
	Bronze		92138	92258	92372
	Stone		92139	92259	92373
	Griege		92195	92364	92374
	Beige		92196	92365	92375
	Black stone		92197	92366	92376
	\$/pc				
TREND COLOR CONCRETE					
RV/	Concrete smoke		92198	92367	92377
	\$/pc				
TREND COLOR METAL					
RV/	Metal dark		92199	92368	92378
	\$/pc				

Individually packaged

CERFIX PROTRIM – EXTERNAL CORNERS


5 pieces per package

		H			
Item	Finish		5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)
ALUMINUM					
RA/	Black anodized		92613	92656	92657
	\$/pc				
TREND COLOR STONE					
RV/	Dark brown		92676	92699	92780
	Ancient gray		92677	92737	92781
	Gray		92678	92738	92782
	Bronze		92679	92739	92783
	Stone		92686	92774	92784
	Griege		92687	92775	92785
	Beige		92688	92776	92786
	Black stone		92689	92777	92787
	\$/pc				
TREND COLOR CONCRETE					
RV/	Concrete smoke		92697	92778	92788
	\$/pc				
TREND COLOR METAL					
RV/	Metal dark		92698	92779	92789
	\$/pc				

No partial packaging

CERFIX PROTRIM – INTERNAL CORNERS

5 pieces per package			H		
Item	Finish		5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)
ALUMINUM					
RA/	Black anodized		92579	92589	92591
\$/pc					
TREND COLOR STONE					
RV/	Dark brown		92806	92845	92860
	Ancient gray		92807	92846	92861
	Gray		92808	92847	92862
	Bronze		92809	92848	92863
	Stone		92839	92849	92864
	Griege		92840	92855	92865
	Beige		92841	92856	92866
	Black stone		92842	92857	92867
\$/pc					
TREND COLOR CONCRETE					
RV/	Concrete smoke		92843	92858	92868
\$/pc					
TREND COLOR METAL					
RV/	Metal dark		92844	92859	92869
\$/pc					
No partial packaging					



CERFIX PROTRIM

Length = 8"10" or 2.7 m
(20 pieces per package)

Length = 8'10" or 2'7 m
(20 pieces per package)

		H								
Item	Finish		3/16" (4.5 mm)	1/4" (6 mm)	5/16" (8 mm)	11/32" (9 mm)	3/8" (10 mm)	7/16" (11 mm)	1/2" (12.5 mm)	9/16" (15 mm)
STAINLESS STEEL										
RI/ \$/pc	Stainless steel AISI 304		92413	92420	92422	92423	92424	92425	92426	92428
RIL/ \$/pc	Superpolished stainless steel AISI 304		92415	92416	92417	–	92418	–	92419	–
RIS/ \$/pc	Satin stainless steel AISI 304		–	92430	92431	92438	92432	92439	92433	92434
RIP/ \$/pc	Sandblasted stainless steel AISI 304		–	92450	92451	92452	92453	92454	92455	–
RIX/ \$/pc	Stainless steel AISI 316		92405	92406	92407	92410	92408	92411	92409	–

Individually packaged - art. RI/15 pack 10 pcs


CERFIX PROTRIM – OUTSIDE CORNER – 5 pieces per package

TIE/ \$/pc	Stainless steel AISI 304		92750	92480	92481	92751	92482	92752	92483	92484
TIEL/ \$/pc	Superpolished stainless steel AISI 304		92790	92792	92794	–	92798	–	92802	–
TIES/ \$/pc	Satin stainless steel AISI 304		–	92485	92486	92753	92487	92754	92488	92489
TIEP/ \$/pc	Sandblasted stainless steel AISI 304		–	92510	92511	92512	92513	92514	92515	–
TIEX/ \$/pc	Stainless steel AISI 316		92500	92501	92502	92755	92503	92756	92504	–

CERFIX PROTRIM – INSIDE CORNER – 5 pieces per package

TII/ \$/pc	Stainless steel AISI 304		92759	92490	92491	92757	92492	92758	92493	92494
TIIL/ \$/pc	Stainless steel superpolished AISI 304		92791	92793	92795	–	92799	–	92803	–
TIIS/ \$/pc	Satin stainless steel AISI 304		–	92495	92496	92760	92497	92761	92498	92499
TIIP/ \$/pc	Sandblasted stainless steel AISI 304		–	92516	92517	92518	92519	92520	92521	–
TIIX/ \$/pc	Stainless steel AISI 316		92505	92506	92507	92762	92508	92763	92509	–

METAL			5/16" (8 mm)	3/8" (10 mm)	7/16" (11 mm)
OUTSIDE CORNER – 5 pieces per package					
TIME/	Polished stainless steel		92960	92964	92966
	\$/pc				
INSIDE CORNER – 5 pieces per package					
TIMI/	Polished stainless steel		92970	92974	92976
	\$/pc				
No partial packaging					



RIN/
RINS/
RINX/

CERFIX PROTRIM N

Length = 8"10" or 2.7 m
(20 pieces per package)

Length = 8'10" or 2.7 m (20 pieces per package)			H		
Item	Finish		5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)
STAINLESS STEEL					
RIN/	Stainless steel AISI 304		92353	92356	92359
	\$/pc				
RINS/	Satin stainless steel AISI 304		92354	92357	92360
	\$/pc				
RINX/	Stainless steel AISI 316		92355	92358	92361
	\$/pc				

Individually packaged

CERFIX PROTRIM N – OUTSIDE CORNER – 5 pieces per package

TIEN/	Stainless steel AISI 304		92813	92816	92819
	\$/pc				
TIENS/	Satin stainless steel AISI 304		92814	92817	92820
	\$/pc				
TIENX/	Stainless steel AISI 316		92815	92818	92821
	\$/pc				

CERFIX PROTRIM N – INSIDE CORNER – 5 pieces per package


TIIN/	Stainless steel AISI 304		92828	92831	92834
	\$/pc				
TIINS/	Satin stainless steel AISI 304		92829	92832	92835
	\$/pc				
TIINX/	Stainless steel AISI 316		92830	92833	92836
	\$/pc				



TIEN/ stainless
steel AISI 304



TIIN/ stainless steel
AISI 304



RLN/
RKN/

PPDesign

CERFIX PROTRIM

Length = 8'10" or 2.7 m
(20 pieces per package)

length = 8'10" or 2.7 m (20 pieces per package)			H			
Item	Finish		1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)
POLISHED BRASS						
RLN/	Polished		92465	92466	92467	92468
	\$/pc					
CHROMIUM-PLATED BRASS						
RKN/	Chromium plated		92469	92470	92471	92472
	\$/pc					

Individually packaged. Items RLN/10, RLN/12,5, RKN/10, RKN/12,5 packaging of 10 pcs

CERFIX PROTRIM – OUTSIDE/INSIDE CORNERS

5 pieces per package

5 pieces per package			H			
Item	Finish		1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)
OUTSIDE CORNERS FOR RLN/ ARTICLES						
ALUMINUM						
TB/	Bright polished gold		92700	92702	92704	92706
	\$/pc					
INSIDE CORNERS FOR RLN/ ARTICLES						
ALUMINUM						
TIB/	Bright polished gold		92585	92586	92587	92588
	\$/pc					

No partial packaging

5 pieces per package

OUTSIDE CORNERS IN SUPERPOLISHED STAINLESS STEEL FOR RKN/ ITEMS


STAINLESS STEEL						
TIEL/ \$/pc	Superpolished stainless steel AISI 304		92792	92794	92798	92802
INSIDE CORNERS IN SUPERPOLISHED STAINLESS STEEL FOR RKN/ ITEMS						
STAINLESS STEEL						
TIIL/ \$/pc	Superpolished stainless steel AISI 304		92793	92795	92799	92803



TIEL/



TIIL/



RPA/

CERFIX PROTRIM

Length = 8"10" or 2.7 m
(20 pieces per package)


		H		
		CO-EXTRUDED PVC		
Item	Finish	1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)
RPA/	Snow white	 80640	80641	80642
	White	 80644	80645	80646
	Cream white RAL 9001	 80648	80649	80650
	Ivory RAL 1015	 80652	80653	80654
	Beige gray RAL 1019	 80656	80657	80658
	Stone gray RAL 7030	 80660	80661	80662
	Ash gray RAL 7038	 80664	80665	80666
	Light gray RAL 7035	 80668	80669	80670
	Beige bahama	 80680	80681	80682
	Brown	 80692	80693	80694
\$ /pc				

No partial packaging

CERFIX PROTRIM

12 pieces per package

12 pieces per package				H			
TPAE/				TPAI/			
POLYPROPYLENE							
OUTSIDE CORNER					INSIDE CORNER		
Finish		1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)
Snow white		80700	80701	80702	80753	80751	80752
White		80703	80704	80705	80750	80754	80755
Cream white RAL 9001		80706	80707	80708	80756	80757	80758
Ivory RAL 1015		80709	80710	80711	80759	80760	80761
Beige gray RAL 1019		80712	80713	80714	80762	80763	80764
Stone gray RAL 7030		80715	80716	80717	80765	80766	80767
Ash gray RAL 7038		80718	80719	80720	80768	80769	80770
Light gray RAL 7035		80721	80722	80723	80771	80772	80773
Beige bahama		80730	80731	80732	80780	80781	80782
Brown		80739	80740	80741	80789	80790	80791
\$ /pc							



RE/

CERFIX PROTRIM

Length = 8'10" or 2.7 m
(20 pieces per package)

		H			
		PVC			
Item	Finish	1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)
	Snow white	79996	79997	79998	79999
	White	80100	80101	80102	80103
	Cream white RAL 9001	80104	80105	80106	80107
	Ivory RAL 1015	80108	80109	80110	–
	Beige gray RAL 1019	80112	80113	80114	–
	Stone gray RAL 7030	80116	80117	80118	–
	Ash gray RAL 7038	80120	80121	80122	–
	Light gray RAL 7035	80124	80125	80126	80127
	Anthracite	80175	80176	80177	–
	Blue	80160	80161	80162	–
	Pastel blue	80140	80141	80142	–
	Light green	80179	80180	80181	–
RE/	Red RAL 3002	80128	80129	80130	–
	Black RAL 9005	80132	80133	80134	–
	Yellow RAL 1023	80136	80137	80138	–
	Pastel pink	80144	80145	80146	–
	Beige bahama	80150	80151	80152	–
	Peach	80154	80155	80156	–
	Caramel	80164	80165	80166	–
	Brown	80168	80169	80170	–
	Dark brown	80172	80173	80174	–
	Coral red	80187	80188	80189	–
	Raw sienna	80191	80192	80193	–
	Terracotta	80195	80362	80194	–
\$/pc					


CERFIX PROTRIM

12 pieces per package

12 pieces per package		H				H			
Item		TE/				TEI/			
Finish		POLYPROPYLENE							
		OUTSIDE CORNER				INSIDE CORNER			
		1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)	1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)	1/2" (12.5 mm)
Snow white		80396	80397	80398	80399	79800	79801	79802	79803
White		80400	80401	80402	80403	79804	79805	79806	79807
Cream white RAL 9001		80404	80405	80406	80407	79808	79809	79810	79811
Ivory RAL 1015		80408	80409	80410	–	79812	79813	79814	–
Beige gray RAL 1019		80412	80413	80414	–	79816	79817	79818	–
Stone gray RAL 7030		80416	80417	80418	–	79820	79821	79822	–
Ash gray RAL 7038		80420	80421	80422	–	79824	79825	79826	–
Light gray RAL 7035		80424	80425	80426	80427	79828	79829	79830	79831
Anthracite		80479	80480	80481	–	79875	79876	79877	–
Blue		80470	80471	80472	–	79848	79849	79850	–
Pastel blue		80440	80441	80442	–	79844	79845	79846	–
Light green		80475	80476	80477	–	79879	79880	79881	–
Red RAL 3002		80428	80429	80430	–	79832	79833	79834	–
Black RAL 9005		80432	80433	80434	–	79836	79837	79838	–
Yellow RAL 1023		80436	80437	80438	–	79840	79841	79842	–
Pastel pink		80444	80445	80446	–	79852	79853	79854	–
Beige bahama		80448	80449	80450	–	79856	79857	79858	–
Peach		80452	80453	80454	–	79860	79861	79862	–
Caramel		80458	80459	80460	–	79864	79865	79866	–
Brown		80462	80463	80464	–	79868	79869	79870	–
Dark brown		80466	80467	80468	–	79872	79873	79874	–

Coral red		80483	80484	80485	–	79887	79888	79889	–
Raw sienna		80487	80488	80489	–	79891	79892	79893	–
Terracotta		80491	80492	80493	–	79895	79896	79897	–
\$ / pc									

No partial packaging



RECO/

PROTRIM ECO

Length = 8'6" or 2.6 m
(80 pieces per package)


H

Item	Finish		1/4" (6 mm)	5/16" (8 mm)	3/8" (10 mm)
RECO/ /80	Snow white		79400	79401	79402
	White		79403	79404	79405
	Cream white RAL 9001		79406	79407	79408
	Ivory RAL 1015		79409	79410	79411
	Ash gray RAL 7038		79412	79413	79414
	Light gray RAL 7035		79415	79416	79417
	Beige bahama		79418	79419	79420

\$ / pc

No partial packaging

Other colors upon request for a minimum 1,000 pieces per color



REC/

PROTRIM ECO

Width = 8'6" or 2.6 m
(100 pieces per package)

ECOLINE PVC

Item	Finish		5/16" (8 mm)	3/8" (10 mm)
REC/ /100	Snow white		79601/100	79602/100
	Cream white RAL 9001		79605/100	79606/100
	Ivory RAL 1015		–	79610/100
	Beige gray RAL 1019		–	79614/100
	Stone gray RAL 7030		–	79618/100
	Ash gray RAL 7038		–	79622/100
	Light gray RAL 7035		–	79626/100
	Beige bahama		–	79642/100

\$ / pc

No partial packaging

Other colors upon request for a minimum 1,000 pieces per color

ADDITIONAL INFORMATION

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: May 29, 2024 MK 13209 / 13210 / 13329 (24-1624)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.
All Rights Reserved. © 2024 MAPEI Corporation.

