

TERMINAL RC / TERMINAL RC FLEX

Profiles for wood and laminate floors



DESCRIPTION

RC is a range of edging profiles for floating wood, laminate or LVT floors designed to allow the necessary expansion.

The assortment of materials and finishes available, including anodized aluminium and natural aluminium coated with Alcrom® Plus (a film reproducing the different shades and/or finishes of wood) provide an aesthetic solution that will match almost any type of flooring in domestic or public settings.

RC is also available in a **Flex** version designed specifically for situations in which the profile has to be shaped using the **Proflex Machine** to match the curved edge of the joint.

MATERIALS

Anodized aluminium

Al-Mg-Si aluminium, heat-treated in T6 (6060 T6).

The profiles are made by extrusion then anodized with a $\geq 15 \mu\text{m}$ thick layer.

The outer surface must be protected from scratches and rubbing. They present a strong resistance to chemical and atmospheric agents. When wet, concrete and its derivatives produce alkaline substances which can corrode metal (forming aluminium hydroxide) when allowed to react with the surface. For this reason, the visible surface of the profile must be quickly and delicately cleaned to remove any concrete, adhesive or grouting substances and detergents.

Anodized surfaces can become ruined through wear and foot traffic (profiles used on floors) and the original finish lost as a result.

Alcrom® Plus coated natural aluminium

Al-Mg-Si aluminium, heat-treated in T6 (6060 T6).

The profiles are extruded then coated with hard-wearing Alcrom® Plus film reproducing the different tones and/or finishes of wood.

General note on metals

Aluminium is not resistant to all chemical compounds. Consequently, contact with particularly aggressive products like hydrochloric acid (HCl) and phosphoric acid (H₃PO₄) should be avoided.

Products generally used to clean stone, ceramic and porcelain tiles, such as muriatic acid, ammonia and bleach, damage the surface finish on the metal and can cause intense corrosion. Moreover, any residues of concrete, adhesive, and grouting materials must always be removed from the surface of the profiles as quickly and delicately as possible.

If adhesive tape is used to cover the profile, it must not be left any longer than an hour.

FIXING

Laying methods

Remove the profile from the packaging.

Check that the depth of the covering to be laid is not greater than the depth of the profile (see label).

Where present, also remove any protection (protective and/or shrink-wrapped film) added to protect the finish.

Measure the length required and cut the profile to this length using an appropriate tool.

After cutting the profile to the right length, place in position and use a permanent marker to mark the exact position of the holes on the profile flange where holes should be drilled.

Remove the profile and drill the floor in the exact positions that you marked previously being careful to check the exact size of the plugs needed.

Slot the plugs into the holes drilled in the floor, reposition the profile correctly and fix it to the wall using the right type of screws making sure that the support surface is perfectly clean.

CARE AND MAINTENANCE

Care and maintenance procedures for the materials used to make these profiles depends largely on the type of alloy and/or finish used.

The instructions provided below describe the operations to be performed on the profile to restore it as much as possible to its original condition.

The purpose of this document is to provide as many general indications as possible to guide you on when and how to clean the product, but they should also be verified on a case-by-case basis.

It should be pointed out there are specific responsibilities in each part of the product's life cycle, starting from when it is installed the first time.

Aluminium

No special maintenance is required and aluminium products can be easily treated with colourless alcohol in a water solution or using ordinary detergents, provided they do not contain acid (hydrochloric or hydrofluoric).

Detergent products made by multiple manufacturers and sold under a variety of commercial brands can generally be used for cleaning.

Generally speaking, there are three types of products:

- Alkaline

- Neutral
- Acid

For cleaning purposes, we recommend using a neutral detergent diluted in water then rinsing with water only, using a non-abrasive sponge and/or cloth to avoid scratching and/or damaging the anodized surface.

During cleaning, the following aspects must be kept in mind at all times:

- Do not use acid or alkaline detergents because they could damage the aluminium;
- Do not use products and/or abrasive materials;
- Do not use organic solvents on painted surfaces;
- Do not use detergents without first checking their chemical composition;
- Do not apply detergents straight onto the surface to be cleaned;
- Surfaces must be "cold" (max T° = 30°C) during cleaning and not exposed to direct sunlight;
- Detergents used in cleaning must also be "cold" (max T° = 30°C) and steam sprays should not be used.

In any case, the final stage in the cleaning process is always sufficient rinsing of the parts treated with water. They must then be immediately dried using soft fabric or leather cloths. Polishes or similar products are not required.

Clean profiles carefully as soon as required, following the instructions on the product package, to prevent any residues of concrete, grout or similar substances from attacking the surface.

FIRE PREVENTION MEASURES

In the event of fire, use chemical fire extinguishers, dry sand or solid extinguishing agents.

NOTES

These profiles must be handled with caution, being careful to wear suitable gloves to prevent injury and/or cuts to the hands.


The instructions and specifications provided here are the product of our experience but are only a guide, should not be considered exhaustive and must be confirmed by extensive practical applications.

Profilpas declines any responsibility for damage to people or things resulting from improper use of the product.

Users must establish for themselves if the product is suitable for the required used and they bear full responsibility for any incorrect installation of the material.

RC

length = 270 cm - pack 20 pcs							
ART.	finishing		7	9	11	13	15
ALUMINIUM							
RC/ F	silver anodised		67407	67477	67547	67617	67687
	gold anodised		-	67487	-	-	-
	bronze anodised		-	67497	-	-	-



RC/ /F
RCF/



RCF/ silver anodised aluminium

length = 270 cm - pack 10 pcs						H
ART.	finishing	7	9	11	13	15
ALUMINIUM covered with ALCROM® PLUS film						
	 10	-	66731	-	-	-
	 20	-	66734	-	-	-
	 38	-	66739	-	-	-
RC/ /F	 40	-	66740	-	-	-
	 42	-	66758	-	-	-
	 65	-	66747	-	-	-
	 78	-	66751	-	-	-
	 80	-	66752	-	-	-

RC

length = 90 cm - pack 10 pcs / blister 			H			
			7	9	11	15
ART.	finishing		RC/47/CV	RC/49/CV	RC/411/CV	RC/415/CV
ALUMINIUM						
	silver anodised		42782	41832	41877	42822
	gold anodised		-	41839	-	-

PRO FLEX LINE

TERMINAL FLEX

length = 270 cm - pack 10 pcs					H		
ART.	finishing		7	9	11	15	22,5
ALUMINIUM							
RCF/	silver anodised		67710	67712	67714	67718	67722

Customized PDS decors on request

individually packed

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: October 31, 2023 MK 13337 (24-2086)

For the most current product data and BEST-BACKEDSM warranty information, visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.

