

PVC LINE 8605-8606-8615-8616

Skirting



DESCRIPTION

PVC Line 8605, 8606, 8615 and 8616 are a range of a non-toxic and shockproof coextruded PVC (expanded + rigid) skirting board, foiled with UV resistant Alcom® Plus decorative film.

They must be laid using suitable adhesives (type PP/96).

The **PVC Line 8605** series is available in 58 different colors, both plain color and wood decoration, in order to suit any type of floor decor. PDS technology also allows customization on demand with infinite solutions.

In addition to the decorative function, it meets the technical requirement to hide the perimeter expansion space in floating flooring.

PVC Line 8605, 8616, 8615 and 8616 does not contain formaldehyde (UNI EN 717-2 1996:1996), can be used in humid environments (water absorption <1% UNI EN ISO 62:2008), resists the cold liquid aggression (UNI EN 12720:2009).

MATERIALS

Compound PVC vinyl foam lead-free, self-extinguishing. Stabilized eco-compatible salt-based Ca-Zn.

LAYING

Laying instructions using Adhesives Type PP/96

Take the skirting board out of the packaging.

Measure and cut the skirting board to the required length with the proper tools.

Verifying that the laying area is perfectly clean and then place the skirting board, now cut to measure, in the correct position, fixing it to the wall with the appropriate adhesive (type PP/96).

Keep sufficiently pressure for a few minutes on the entire length of the skirting board in order to ensure sufficient adhesion to the laying surface.

CARE AND MAINTENANCE

The instructions below describe the operations in order to maintain as much as possible the original appearance of the product.

The intent is to provide all those general guidelines that can serve in the choice of when and how to clean, but they will have to be checked case by case. It must be underlined that, at every stage of product life starting from its installation, there are already definite responsibilities.

PVC

These need no particular maintenance and are easily cleaned with colorless alcohol diluted in water, or with normal detergents diluted in water (though not acid-based products); rinse thoroughly when finished, with water only.

Use a sponge and/or non-abrasive cloth to prevent scratches and/or damage to the surface.

FIRE CONTROL MEASURES

In case of fire, extinguish with fire-fighting chemical products, dry sand or solid fire-extinguishing agents.

NOTE

These profiles must be handled with care, taking the necessary steps to use suitable gloves to prevent wounds, such as cuts to the hand.


All indications and instructions herein contained, that comes from our own experience, has to be understood as purely informative and will have to be confirmed through exhaustive practical experience.

Profilpas will not be held responsible for any personal injury or material damage from improper use of the product.


The user is responsible for establishing whether the product is suitable for the task and likewise must assume all responsibility for incorrect laying of material



8606 white RAL 9003 co-extruded PVC



8605



8605 covered with
Alcrom® Plus film

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.

8605	☐	white RAL 9003	29175
	☐	white RAL 9010	29177

no partial packaging

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM

ART.


decors

8605	☐	96 white RAL 9010 embossed	29030
	☒	97 black RAL 9005 embossed	29031
8605	☒	99 satin silver	29035
	☐	100 satin steel	29036

no partial packaging



8605 foam PVC covered with Alcrom® Plus film



8606

PVC LINE

length = 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM

ART.	decors		decors		decors		decors	
8605	02	29000	41	29012	1006	29102	1060	29120
	08	29001	44	29013	1009	29103	1063	29121
	09	29002	47	29033	1012	29104	1066	29122
	10	29003	48	29015	1021	29107	1069	29123
	11	29004	65	29018	1024	29108	1081	29127
	12	29005	76	29020	1030	29110	1084	29128
	20	29006	77	29021	1033	29111	1087	29129
	25	29032	78	29022	1036	29112	1090	29130
	32	29007	80	29023	1042	29114	1105	29135
	34	29008	81	29024	1045	29115	1108	29136
	35	29009	92	29026	1051	29117	1111	29137
	36	29010	95	29029	1054	29118		
	40	29011	1003	29101	1057	29119		

no partial packaging - 8605 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.			
8606	☐	white RAL 9003	29227
	☐	white RAL 9010	29229


no partial packaging - 8606 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters



8616 black RAL 9004 co-extruded PVC



8615 silver co-extruded PVC



8615

PVC LINE


length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.

8615	☐	white RAL 9003	29353
	☐	white RAL 9010	29355

no partial packaging



8615 decors with
film Alcrom® Plus

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM


ART.

decors

8615	☐	96 white RAL 9010 embossed	29357
	☒	97 black RAL 9005 embossed	29358

no partial packaging

8615 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters



8616

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.

8616	☐	white RAL 9003	29495
------	--------------------------	----------------	-------

no partial packaging

8616 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:

Flooring: 1-800-992-6273

Concrete and heavy construction: 1-888-365-0614

Canada:

1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: November 30, 2023 MK 13366 / 13367 (24-1798)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.

