

UltraCare Cement Grout Haze Remover



DESCRIPTION

UltraCare® Cement Grout Haze Remover is a professional-strength formulation that helps to remove cement grout haze from tile, concrete and stone surfaces. It is an acidic, low-odor, non-flammable, easy-to-use, water-based formula.

FEATURES AND BENEFITS

- Professional-strength formula
- Removes cement grout haze
- Easy-to-use, water-based formula

WHERE TO USE

- Most acid-resistant natural stone surfaces including slate, granite, ceramic and porcelain tiles, as well as quarry tile, brick and sealed Saltillo

LIMITATIONS

- Ensure that the product does not come in contact with any non-recommended surface. It will etch polished marble and limestone, and may lighten the color of cementitious materials.

- Do not mix with other chemicals.
- Do not apply product with a sprayer.

Consult MAPEI's Technical Services Department for application recommendations regarding surfaces and conditions not listed.

INDUSTRY STANDARDS AND APPROVALS

- Meets all EPA and SCAQMD standards for VOCs

SURFACE PREPARATION

- Be sure all surfaces to be treated are swept or vacuumed to remove loose debris.
- For best results, pre-wet the surface with water.

PRODUCT APPLICATION

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

Always test first in several inconspicuous areas to confirm desired results.

1. Avoid skin and eye contact by wearing chemical-resistant gloves and protective lenses.
2. Shake well before using. Do not dilute before applying.
3. Working in a small, manageable area of 15 sq. ft. (1.39 m²), liberally apply an even coat over the required area with a paint brush, mop or paint pad. Do not apply with a sprayer.
4. Immediately remove product from unintended surfaces with a wet cloth to prevent potential damage to those surfaces.
5. Allow product to stand on the surface for 10 to 15 minutes.
6. Do not let *UltraCare* Cement Grout Haze Remover dry on the surface. Keep the surface wet by adding more product.
7. Agitate surface with a soft brush or white scrub pad after testing a small area first to make sure that brush or pad will not scratch the surface. A low-rpm (150 to 300) floor-scrubbing machine may be used for larger and/or commercial installations as needed.
8. Wipe up residual cleaner with clean, dry cloths.
9. Rinse the surface well with clean water and allow to thoroughly dry.
10. If more than one application is required, repeat steps 3 through 9.

Close container tightly after each use. Store in original container only. Store between the temperatures of 35°F to 90°F (2°C to 32°C). Do not allow to freeze.

For ongoing maintenance instructions, see the "*UltraCare* Maintenance Guide" in the *UltraCare* Stone, Tile, Grout Care and Maintenance Solutions section of MAPEI's Website.

Shelf Life and Application Properties

Shelf life	Up to 3 years when stored in original, unopened packaging at 73°F (23°C)
Appearance	Clear
Odor	Slight odor
Physical state	Liquid
VOC content (California Air Resources Board's Consumer Products Regulation, Section 94509)	< 5% by weight
Typical VOC content per California Air Resources Board testing methods	0.00% by weight

Packaging

Size
Bottle: 1 U.S. qt. (946 mL)

Approximate Coverage*

Size	Coverage
1 U.S. qt. (946 mL)	20 to 50 sq. ft. (1.86 to 4.65 m ²)

* Coverage will vary depending on density, porosity, texture, surface absorption, time that solution is left on surface, application method and severity of the problem.

ADDITIONAL INFORMATION

Refer to the Safety Data Sheet (SDS) for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:

Flooring: 1-800-992-6273

Concrete and heavy construction: 1-888-365-0614

Canada:

1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: March 26, 2026 MK 3000077 (26-1444)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.
All Rights Reserved. © 2026 MAPEI Corporation.

