

Planipatch Plus

High-Performance Additive for *Planipatch*®



DESCRIPTION

Planipatch Plus® is an acrylic latex additive for use specifically with *Planipatch* fast-setting, polymer-modified, cement-based patching compound. Mixing *Planipatch Plus* undiluted with *Planipatch* allows it to be used over a variety of substrates including vinyl composition tile (VCT), felt-backed sheet vinyl, cutback adhesive residue and MAPEI moisture barriers.

FEATURES AND BENEFITS

- Enhances bond of *Planipatch* to select nonporous substrates
- Improves the flexibility of *Planipatch*

WHERE TO USE

- As an additive only for *Planipatch*. For details, see the current Technical Data Sheet (TDS) for *Planipatch*.

LIMITATIONS

- Do not mix *Planipatch Plus* (neat or diluted) with anything other than *Planipatch*.

MIXING

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

- Use the following mixing ratios for *Planipatch Plus*, depending on the functionality required:

Diluted mixing

- The dilution ratio is 1 part of *Planipatch Plus* to 3 parts of water. To dilute a *Planipatch Plus* jug measuring 1 U.S. gal. (3.79 L), mix in 3 U.S. gals. (11.4 L) of water. Add the 4 U.S. gals. (15.1 L) diluted mixture to nine 10-lb. (4.54 kg) bags of *Planipatch* powder.

Full-strength mixing

- When used at full strength, a *Planipatch Plus* jug measuring 1 U.S. gal. (3.79 L) mixes with two 10-lb. (4.54 kg) bags of *Planipatch* powder.

APPLICATION

See the current TDS for *Planipatch*.

Shelf Life and Application Properties

at 73°F (23°C) and 50% relative humidity

Shelf life	2 years when stored in original, unopened container
Color	Milky white
pH	5 to 7
Solids content	35% to 45%
Density	8.5 lbs. per U.S. gal. (1.03 g per L)
VOC content (SCAQMD)	Not regulated
Typical VOC content per SCAQMD Rule 1168 testing methods	3 g per L

Protect containers from freezing in transit and storage. Provide for heated storage on site and deliver all materials at least 24 hours before work begins.

Packaging

Size
Jug: 1 U.S. gal. (3.79 L)
Pail: 5 U.S. gals. (18.9 L)

RELATED DOCUMENTS

- Reference guide: "Surface-Preparation Requirements: Resilient/Carpet Adhesives"*

*At www.mapei.com

ADDITIONAL INFORMATION

Refer to the Safety Data Sheet (SDS) for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: October 2, 2025 MK 3000156 (25-2311)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.
All Rights Reserved. © 2025 MAPEI Corporation.

