

# Mapeheat Temperature Sensing Probe

Sensing Probe for Thermostat-Controlled Radiant-Heated Floors



Technology from • Technologie de • Tecnologia de

**Nuheat**

## DESCRIPTION

Mapeheat™ Temperature Sensing Probe is designed for use with Mapeheat Thermo Connect, Mapeheat Thermo Touch and Mapeheat Thermo Basic thermostats. Use this replacement product if the probe that accompanies a Mapeheat thermostat is misplaced or if an additional probe is desired.

Note that the temperature-sensing probe must be installed before installation of the finished flooring.

## INSTALLATION

To ensure full functionality of the floor-sensing thermostat, it is vital to install the probe before a mortar or self-leveler is applied on top. For instructions on installing the probe, see the *Mapeheat Cable* or *Mapeheat Mat* Installation Handbook as well as the Quick Start Guide for the selected thermostat, all of which can be found inside product packaging. Failure to install the probe will render thermostat's floor-sensing capabilities inoperable.

### Product Specifications

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Probe length | 15 ft. (4.57 m)                                                           |
| Packaging    | Plastic bag includes precision screwdriver for thermostat screw terminals |

## RELATED DOCUMENTS

---

- *Mapeheat Cable* Installation Handbook\*
- *Mapeheat Mat* Installation Handbook\*
- Quick Start Guide for the selected *Mapeheat* thermostat\*\*

\* At [www.mapei.com](http://www.mapei.com)

\*\* Provided inside packaging

## ADDITIONAL INFORMATION

---

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact [sustainability\\_USA@mapei.com](mailto:sustainability_USA@mapei.com) (USA) or [sustainability-durabilite@mapei.com](mailto:sustainability-durabilite@mapei.com) (Canada).

## WARNING

---

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

#### LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at [www.mapei.com](http://www.mapei.com). **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

## CONTACT INFORMATION

### MAPEI Headquarters of North America

1144 East Newport Center Drive  
Deerfield Beach, Florida 33442  
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

### Technical Services

U.S. and Puerto Rico:

Flooring: 1-800-992-6273

Concrete and heavy construction: 1-888-365-0614

Canada:

1-800-361-9309

### Customer Service

1-800-42-MAPEI (1-800-426-2734)

**Edition Date: July 23, 2025 MK 3000360 (25-2198)**

For the most current product data and BEST-BACKED<sup>SM</sup> warranty information,  
visit [www.mapei.com](http://www.mapei.com).  
All Rights Reserved. © 2025 MAPEI Corporation.

