

Mapefloor DQ

Decorative Quartz for Broadcasting into Resinous Flooring Systems



DESCRIPTION

Mapefloor™ DQ is a medium-grade aggregate used for broadcasting into resinous flooring systems.

FEATURES AND BENEFITS

- Chemically compatible with several resin formulations
- Available in a variety of solid colors and unique color blends

WHERE TO USE

- Healthcare facilities
- Commercial and general-service industrial environments
- Department stores
- Government buildings
- Educational institutions such as colleges and universities

PRODUCT APPLICATION

- Broadcast *Mapefloor DQ* into the resinous flooring system to saturation. Broadcast in a manner so that *Mapefloor DQ* falls vertically into the resin. Broadcast to the maximum fill rate. This will provide a completed

application, resulting in a dry broadcast of *Mapefloor DQ* that covers the entire surface.

STORAGE

- *Mapefloor DQ* should be kept in a sealed container, to avoid being exposed to contaminants, and kept in an area with low humidity at room temperature.

Shelf Life and Product Characteristics

Shelf life	No expiration of shelf life when stored in original, unopened packaging
Physical state	Aggregate
Colors	Refer to MAPEI's <i>Mapefloor DQ</i> color chart at www.mapei.com .
Size	32 mesh

Packaging

Size
Bag: 50 lbs. (22.7 kg)

ADDITIONAL INFORMATION

Refer to the Safety Data Sheet (SDS) for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:

Flooring: 1-800-992-6273

Concrete and heavy construction: 1-888-365-0614

Canada:

1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: January 12, 2026 MK 3008900 (25-2689)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.
All Rights Reserved. © 2026 MAPEI Corporation.

