

Safety Data Sheet

DILUENTE M33

Safety Data Sheet dated: 10/10/2025 - version 2

Date of first edition: 01/15/2024



1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: DILUENTE M33

Trade code: 9010483

Recommended use of the chemical and restrictions on use

Recommended use: Solvent based thinner

Restrictions on use: Data not available.

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flammable Liquids — Category 3

Flammable liquid and vapour.

Acute toxicity (inhalation), Category 4

Harmful if inhaled.

Skin irritation, Category 2

Causes skin irritation.

Eye irritation, Category 2A

Causes serious eye irritation.

Specific target organ toxicity following single exposure, Category 3

May cause respiratory irritation.

Specific target organ toxicity following single exposure, Category 3

May cause drowsiness or dizziness.

Aspiration hazard, Category 1

May be fatal if swallowed and enters airways.

Chronic (long term) aquatic hazard, category 2

Toxic to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P240 Ground and bond container and receiving equipment.

P241	Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharge.
P261	Avoid breathing mist/vapours/spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/clothing and eye/face protection.
P301+P310	IF SWALLOWED: Immediately call a doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a doctor if you feel unwell.
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with applicable regulations.

Hazards associated with foreseeable chemical reactions

None

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥30 - <36 %	naphthenic oil; Low boiling point naphtha - unspecified	CAS:64742-95-6, 128601-23-0 EC:265-199-0 EU CLP Index:649-356-00-4	STOT SE 3, H335; STOT SE 3, H336; Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411
≥30 - <36 %	propylene glycol monomethyl ether; 1-methoxy-2-propanol	CAS:107-98-2 EC:203-539-1 EU CLP Index:603-064-00-3	Flam. Liq. 3, H226; STOT SE 3, H336
≥30 - <36 %	2-butoxyethanol; ethylene glycol monobutyl ether	CAS:111-76-2 EC:203-905-0 EU CLP Index:603-014-00-0	Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319
≥5 - <10 %	n-butyl acetate; acetic acid, butyl ester	CAS:123-86-4 EC:204-658-1 EU CLP Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

- In case of fire, use a dry powder fire extinguisher to extinguish.

Unsuitable extinguishing media:

- None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: Not available
- Explosive properties: Not available
- Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.
-

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove all sources of ignition.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Provide adequate ventilation.
- Use appropriate respiratory protection.
- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
 - Retain contaminated washing water and dispose it.
-

7. HANDLING AND STORAGE

Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.
 Use localized ventilation system.
 Don't use empty container before they have been cleaned.
 Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 Contaminated clothing should be changed before entering eating areas.
 Do not eat or drink while working.
 See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
 Store in a well-ventilated place. Keep cool.
 Avoid direct exposure to sunlight.
 Opened containers must be carefully resealed and kept upright to prevent leakage.
 Flammable mixtures may accumulate within the headspace of containers at room temperature.
 Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.
 Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.
 Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Electrical installations / working materials must comply with the technological safety standards.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
propylene glycol monomethyl ether; 1-methoxy-2-propanol CAS: 107-98-2	ACGIH		Long Term: 50 ppm; Short Term: 100 ppm A4 - Eye and URT irr
	MAK	GERMANY	Long Term: 370 mg/m3 - 100 ppm
	ACGIH		Long Term: 50 ppm; Short Term: 100 ppm A4 - Not Classifiable as a Human Carcinogen; eye and upper respiratory tract irritation
	MAK	AUSTRIA	Long Term: 187 mg/m3 - 50 ppm; Short Term: 187 mg/m3 - 50 ppm
	MAK	SWITZERLAND	Long Term: 360 mg/m3 - 100 ppm
2-butoxyethanol; ethylene glycol monobutyl ether CAS: 111-76-2	MAK	AUSTRIA	Short Term: Ceiling - 187 mg/m3 - 50 ppm
	EU		Long Term: 375 mg/m3 - 100 ppm; Short Term: 563 mg/m3 - 150 ppm Skin
	MAK	GERMANY	Long Term: 49 mg/m3 - 10 ppm
	OSHA		Long Term: 240 mg/m3 - 50 ppm prevent or reduce skin absorption;
	ACGIH		Long Term: 20 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans; eye and upper respiratory tract irritation;
	MAK	AUSTRIA	Long Term: 98 mg/m3 - 20 ppm; Short Term: 200 mg/m3 - 40 ppm
	MAK	SWITZERLAND	Long Term: 49 mg/m3 - 10 ppm
		D	

	OSHA	Long Term: 240 mg/m3 - 50 ppm prevent or reduce skin absorption
	ACGIH	Long Term: 20 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans; eye and upper respiratory tract irritation
	EU	Long Term: 98 mg/m3 - 20 ppm; Short Term: 246 mg/m3 - 50 ppm Skin
n-butyl acetate; acetic acid, butyl ester CAS: 123-86-4	ACGIH	Long Term: 710 mg/m3
	MAK	Long Term: 950 mg/m3
	OSHA AUSTRALIA	Short Term: Ceiling - 950 mg/m3 - 150 ppm
	ACGIH	Long Term: 713 mg/m3 - 50 ppm
	MAK AUSTRIA	Long Term: 200 mg/m3 - 100 ppm; Short Term: 480 mg/m3
	MAK SWITZERLAND	Long Term: 480 mg/m3 - 100 ppm; Short Term: 960 mg/m3 - 200 ppm
	EU	Long Term: 241 mg/m3 - 50 ppm; Short Term: 723 mg/m3 - 150 ppm

Biological limit values

2-butoxyethanol; ethylene glycol monobutyl ether
CAS: 111-76-2

Biological Indicator: butoxyacetic acid (BAA); Sampling Period: End of turn
Value: 200 MGGCREAT; Medium: Urine

Predicted No Effect Concentration (PNEC) values

propylene glycol monomethyl ether; 1-methoxy-2-propanol
CAS: 107-98-2

Exposure Route: Fresh Water; PNEC Limit: 10 mg/l

Exposure Route: Intermittent release; PNEC Limit: 100 mg/l

Exposure Route: Marine water; PNEC Limit: 1 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 52,3 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 5,2 mg/kg

Exposure Route: Soil; PNEC Limit: 4,59 mg/kg

n-butyl acetate; acetic acid, butyl ester
CAS: 123-86-4

Exposure Route: Fresh Water; PNEC Limit: 1,18 mg/l

Exposure Route: Marine water; PNEC Limit: 0,018 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0,981 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0,0981 mg/kg

Exposure Route: Intermittent release; PNEC Limit: 0,36 mg/l

Exposure Route: Soil; PNEC Limit: 0,0903 mg/kg

Derived No Effect Level (DNEL) values

propylene glycol monomethyl ether; 1-methoxy-2-propanol
CAS: 107-98-2

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 369 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 553,5 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 553,5 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 183 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 43,9 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 78 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 33 mg/m3

n-butyl acetate; acetic
acid, butyl ester
CAS: 123-86-4

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 960 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Industry: 960 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 480 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 480 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Consumer: 859,7 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Consumer: 859,7 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 102,34 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Consumer: 102,34 mg/m3

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and colour:	liquid transparent
Odour:	characteristic
Odour threshold:	No data available
Melting point / freezing point:	No data available
Initial boiling point and boiling range:	120 °C (248 °F)
Flammability:	The product is classified Flam. Liq. 3
Upper/lower flammability or explosive limits:	No data available
Flash point:	35 °C (95 °F)
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available

Viscosity:	No data available
Kinematic viscosity:	<= 20,5 mm2/sec (40 °C)
Solubility in water:	No data available
Solubility in oil:	No data available
Partition coefficient (n-octanol/water):	No data available
Vapour pressure:	No data available
Evaporation rate:	No data available
Relative density:	0.89 g/cm3
Vapour density:	No data available

Particle characteristics:

Particle size:	No data available
----------------	-------------------

Other information

Explosive properties:	No data available
Oxidizing properties:	No data available
Solid/gas flammability:	No data available
Substance Groups relevant properties:	No data available
Miscibility:	No data available
Fat Solubility:	No data available
Conductivity:	No data available

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	The product is classified: Acute toxicity (inhalation), Category 4(H332) ATEmix - Inhalation (Mist) : 1.6129 mg/l
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met

h) STOT-single exposure	The product is classified: Specific target organ toxicity following single exposure, Category 3(H335), Specific target organ toxicity following single exposure, Category 3(H336)
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	The product is classified: Aspiration hazard, Category 1(H304)

Toxicological information on main components of the mixture:

naphthenic oil; Low boiling point naphtha - unspecified	a) acute toxicity	LD50 Skin Rabbit > 2000 mg/kg LD50 Oral Rat = 3492, mg/kg LC50 Inhalation Vapour Rat = 6193, mg/m3
propylene glycol monomethyl ether; 1-methoxy-2-propanol	a) acute toxicity	LD50 Oral Rat = 5300 mg/kg LD50 Skin Rabbit = 13000 mg/kg LC50 Inhalation Rat = 28,8 mg/l 4h LD50 Skin Rabbit = 13 g/kg LC50 Inhalation Rat > 7559 ppm 6h LD50 Oral Rat = 5000 mg/kg
	h) STOT-single exposure	NOAEL Oral Rat = 919 mg/kg NOAEL Inhalation Rat = 3,7 mg/kg NOAEL Skin Rabbit > 1000 mg/kg
2-butoxyethanol; ethylene glycol monobutyl ether	a) acute toxicity	LD50 Oral Guinea pig = 1414, mg/kg
n-butyl acetate; acetic acid, butyl ester	a) acute toxicity	LC50 Inhalation Rat = 21,1 mg/l 4h LD50 Oral Rat > 6400 mg/kg LD50 Skin Rabbit > 5000 mg/kg LD50 Skin Rabbit > 17600 mg/kg LC50 Inhalation Rat = 390 ppm 4h LD50 Oral Rat = 10768 mg/kg
	g) reproductive toxicity	NOAEC = 2000 ppm

Substance(s) listed on the IARC Monographs:

2-butoxyethanol; ethylene glycol monobutyl ether Group 3

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Chronic (long term) aquatic hazard, category 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
naphthenic oil; Low boiling point naphtha - unspecified	CAS: 64742-95-6, 128601-23-0 - EINECS: 265-199-0 - INDEX: 649-356-00-4	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 9,22 mg/L 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 21,3 mg/L 48h IUCLID
propylene glycol monomethyl ether; 1-methoxy-2-propanol	CAS: 107-98-2 - EINECS: 203-539-1 - INDEX: 603-064-00-3	a) Aquatic acute toxicity : LC50 Fish = 5000 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 23300 mg/L 48 a) Aquatic acute toxicity : EC50 Algae > 1000 mg/L 96 a) Aquatic acute toxicity : LC50 Bacteria > 1000 mg/L 3 a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 20,8 g/l 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 23300 mg/L 48h IUCLID
2-butoxyethanol; ethylene glycol monobutyl ether	CAS: 111-76-2 - EINECS: 203-905-0 - INDEX: 603-014-00-0	a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 1490 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna > 1000 mg/L 48h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 2950 mg/L 96h IUCLID
n-butyl acetate; acetic acid, butyl ester	CAS: 123-86-4 - EINECS: 204-658-1 - INDEX: 607-025-00-1	a) Aquatic acute toxicity : LC50 Fish = 18 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 44 mg/L 48 a) Aquatic acute toxicity : EC50 Algae = 675 mg/L 72 a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 100 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 17 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 674,7 mg/L 72h IUCLID

Persistence and degradability

Component	Persitence/Degradability:	Duration	Notes:
propylene glycol monomethyl ether; 1-methoxy-2-propanol	Readily biodegradable	28 d	86% - OCSE N.301 E

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of

environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN1263

ADR-UN number: 1263

IATA-Un number: 1263

IMDG-Un number: 1263

UN proper shipping name

DOT-Proper Shipping Name: PAINT RELATED MATERIAL (solvent naphtha)

ADR-Shipping Name: PAINT RELATED MATERIAL (solvent naphtha)

IATA-Technical name: PAINT RELATED MATERIAL (solvent naphtha)

IMDG-Technical name: PAINT RELATED MATERIAL (solvent naphtha)

Transport hazard class(es)

DOT-Hazard Class: 3

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group

DOT Packing Group: III

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: No

Transport in bulk according to IMO instruments

N.A.

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 367, B1, B52, B131, IB3, T2, TP1, TP29

DOT-Label(s): 3

DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID) :

ADR-Label: 3

ADR-Hazard identification number: -

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA) :

IATA-Passenger Aircraft: 355

IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3 A72 A192

Sea (IMDG) :

IMDG-Stowage and handling: Category A

IMDG-Segregation: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisioning: 163 223 367 955
IMDG-EMS: F-E, [S-E]

15. REGULATORY INFORMATION

This Safety Data Sheet has been prepared according to the Hazard Communication Standard 2024 (HCS 2024)

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

naphthenic oil; Low boiling point is listed in TSCA Section 8b
naphtha - unspecified

propylene glycol monomethyl ether; 1-methoxy-2-propanol is listed in TSCA Section 8b

2-butoxyethanol; ethylene glycol monobutyl ether is listed in TSCA Section 8b

n-butyl acetate; acetic acid, butyl ester is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

n-butyl acetate; acetic acid, butyl ester

Section 313 - Toxic chemical list:

2-butoxyethanol; ethylene glycol monobutyl ether

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

n-butyl acetate; acetic acid, butyl ester Reportable quantity: 5000 pounds

CAA - Clean Air Act

CAA listed substances:

propylene glycol monomethyl ether; 1-methoxy-2-propanol is listed in CAA Section 112(b) - HON

2-butoxyethanol; ethylene glycol monobutyl ether is listed in CAA Section 112(b) - HON Section 112(b) - HAP

CWA - Clean Water Act

CWA listed substances:

n-butyl acetate; acetic acid, butyl ester is listed in CWA Section 311

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

No substances listed

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

propylene glycol monomethyl ether; 1-methoxy-2-propanol

2-butoxyethanol; ethylene glycol monobutyl ether

n-butyl acetate; acetic acid, butyl ester

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

propylene glycol monomethyl ether; 1-methoxy-2-propanol

2-butoxyethanol; ethylene glycol monobutyl ether

n-butyl acetate; acetic acid, butyl ester

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

propylene glycol monomethyl ether; 1-methoxy-2-propanol
2-butoxyethanol; ethylene glycol monobutyl ether
n-butyl acetate; acetic acid, butyl ester

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 10/10/2025 - version 2

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/3/Inhal	Acute Tox. 3	Acute toxicity (inhalation), Category 3
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
IMDG: International Maritime Code for Dangerous Goods.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
CLP: Classification, Labeling, Packaging.
EU CLP Index: Index number as reported in Annex VI to EU Reg. 1272/2008
EINECS: European Inventory of Existing Commercial Chemical Substances.
INCI: International Nomenclature of Cosmetic Ingredients.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
GefStoffVO: Ordinance on Hazardous Substances, Germany.
LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 16. OTHER INFORMATION