

Safety Data Sheet

ULTRABOND ECO 975

Safety Data Sheet dated: 09/24/2025 - version 12

Date of first edition: 05/28/2015



1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: ULTRABOND ECO 975

Trade code: 9019456

Recommended use of the chemical and restrictions on use

Recommended use: Polyurethane-based adhesive

Restrictions on use: Not available

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Eye irritation, Category 2A

Causes serious eye irritation.

Respiratory Sensitization, Category 1

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sensitization, Category 1

May cause an allergic skin reaction.

Carcinogenicity, Category 1A

May cause cancer if inhaled.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 May cause cancer if inhaled.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/clothing and eye/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a doctor.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with applicable regulations.

Hazards associated with foreseeable chemical reactions

None

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥2.5 - <3 %	calcium oxide; quicklime	CAS:1305-78-8 EC:215-138-9	STOT SE 3, H335; Skin Irrit. 2, H315; Eye Dam. 1, H318
≥0.6 - <1 %	4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	CAS:101-68-8 EC:202-966-0 EU CLP Index:615-005-00-9	Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334; Skin Sens. 1, H317; STOT RE 2, H373; Carc. 2, H351
≥0.6 - <1 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350
≥0.3 - <0.5 %	4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluene	CAS:4083-64-1 EC:223-810-8 EU CLP Index:615-012-00-7	Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334

The actual concentration of the components listed above is withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.
OBTAIN IMMEDIATE MEDICAL ATTENTION.
Obtain medical attention if skin related symptoms persist.
Remove contaminated clothing immediately and dispose of safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:
(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:
Water.
Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
Hazardous combustion products: Not available
Explosive properties: Not Relevant
Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove persons to safety.
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
calcium oxide; quicklime CAS: 1305-78-8	ACGIH		Long Term: 2 mg/m3 URT irr
	MAK	GERMANY	Long Term: 1 mg/m3
	OSHA		Long Term: 5 mg/m3
	ACGIH		Long Term: 2 mg/m3 upper respiratory tract irritation

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-CAS: 101-68-8]	MAK	AUSTRIA	Long Term: 1 mg/m3; Short Term: 4 mg/m3
	MAK	SWITZERLAND	Long Term: 2 mg/m3
	EU		Long Term: 1 mg/m3; Short Term: 4 mg/m3 Respirable fraction
	ACGIH		Long Term: 0,005 ppm Resp sens
	MAK	GERMANY	Long Term: 0,05 mg/m3
	ACGIH		Long Term: 0,005 ppm respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
	OSHA		Short Term: Ceiling - 0,2 mg/m3 - 0,02 ppm
	MAK	AUSTRIA	Long Term: 0,05 mg/m3 - 0,005 ppm; Short Term: 0,1 mg/m3 - 0,01 ppm
	ACGIH		Long Term: 0,005 ppm respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
	OSHA		Short Term: Ceiling - 0,2 mg/m3 - 0,02 ppm
silica sand; quartz CAS: 14808-60-7	EU		Long Term: 0,006 mg/m3; Short Term: 0,012 mg/m3 Skin; Dermal and respiratory sensitisation
	ACGIH		Long Term: 0,025 mg/m3 A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA	Long Term: 0,15 mg/m3
	ACGIH		Long Term: 0,025 mg/m3 (R), A2 - Pulm fibrosis, lung cancer
	MAK	SWITZERLAND	Long Term: 0,15 mg/m3
	EU		Long Term: 0,1 mg/m3 Behaviour Binding

Predicted No Effect Concentration (PNEC) values

calcium oxide; quicklime CAS: 1305-78-8	Exposure Route: Fresh Water; PNEC Limit: 0,49 mg/l		
	Exposure Route: Marine water; PNEC Limit: 0,32 mg/l		
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3 mg/l		
	Exposure Route: Soil; PNEC Limit: 1080 mg/kg		
	Exposure Route: Soil; PNEC Limit: 816 mg/l		
	Exposure Route: Fresh Water; PNEC Limit: 1 mg/l		
	Exposure Route: Marine water; PNEC Limit: 0,1 mg/l		
	Exposure Route: Soil; PNEC Limit: 1 mg/kg		
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 mg/l		
	Exposure Route: Intermittent release; PNEC Limit: 10 mg/l		

Derived No Effect Level (DNEL) values

calcium oxide; quicklime CAS: 1305-78-8	Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 4 mg/m3; Consumer: 4 mg/m3		
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 1 mg/m3; Consumer: 1 mg/m3		
	Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects Worker Industry: 50 mg/kg		
	Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 0,1 mg/m3		

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Industry: 0,1 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 0,05 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 0,05 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Consumer: 25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Consumer: 0,05 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 20 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Consumer: 0,05 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 0,025 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Consumer: 0,025 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, local effects
Worker Industry: 28,7 mg/cm2; Consumer: 17,2 mg/cm2

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and colour:	paste beige
Odour:	characteristic
Odour threshold:	Not Relevant
Melting point / freezing point:	Not Relevant
Initial boiling point and boiling range:	Not Relevant
Flammability:	Not Relevant
Upper/lower flammability or explosive limits:	Not Relevant
Flash point:	94 °C (201 °F)
Auto-ignition temperature:	Not Relevant
Decomposition temperature:	Not Relevant

pH:	Not Relevant
Viscosity:	110,000.00 mPA-s
Kinematic viscosity:	> 20,5 mm2/sec (40 °C)
Solubility in water:	insoluble
Solubility in oil:	partly soluble
Partition coefficient (n-octanol/water):	Not Relevant
Vapour pressure:	Not Relevant
Evaporation rate:	Not Relevant
Relative density:	1.10 g/cm3
Vapour density:	Not Relevant

Particle characteristics:

Particle size:	No data available
----------------	-------------------

Other information

Explosive properties:	Not Relevant
Oxidizing properties:	Not Relevant
Solid/gas flammability:	Not Relevant
Substance Groups relevant properties:	Not Relevant
Miscibility:	Not Relevant
Fat Solubility:	Not Relevant
Conductivity:	Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	The product is classified: Respiratory Sensitization, Category 1(H334), Skin Sensitization, Category 1(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	The product is classified: Carcinogenicity, Category 1A(H350)

g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

calcium oxide; quicklime	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg LD50 Skin Rat > 2500 mg/kg	
4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg	
	f) carcinogenicity	Carcinogenicity Inhalation Rat = 6, mg/m3	2 y
	g) reproductive toxicity	NOAEL Inhalation Rat = 12, mg/m3	20 d
silica sand; quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg LD50 Skin > 2000 mg/kg	
4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluene	a) acute toxicity	LC50 Inhalation Rat > 640 ppm 1h LD50 Oral Rat = 2234 mg/kg	

Substance(s) listed on the IARC Monographs:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	Group 3
silica sand; quartz	Group 1

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
calcium oxide; quicklime	CAS: 1305-78-8 - EINECS: 215-138-9	a) Aquatic acute toxicity : LC50 Fish = 457 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 49,1 mg/L 48 b) Aquatic chronic toxicity : NOEC Daphnia = 32 mg/L - 14 d

4,4'-methylenediphenyl
diisocyanate; benzene, 1,1'-
methylenebis[4-isocyanato-

CAS: 101-68-8 -
EINECS: 202-
966-0 - INDEX:
615-005-00-9

- a) Aquatic acute toxicity : LC50 Fish = 50,6 mg/L 96
- a) Aquatic acute toxicity : LC50 Daphnia = 158 mg/L 96
- a) Aquatic acute toxicity : EC50 Algae = 184,57 mg/L 72
- b) Aquatic chronic toxicity : NOEC Algae = 48 mg/L 72
- a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 1070 mg/L 96h IUCLID
- a) Aquatic acute toxicity : LC50 Fish > 1000 mg/L 96
- a) Aquatic acute toxicity : EC50 Daphnia > 1000 mg/L 24
- b) Aquatic chronic toxicity : NOEC Daphnia > 10 mg/L - 21 d
- a) Aquatic acute toxicity : EC50 Algae > 1640 mg/L 72
- c) Bacteria toxicity : EC50 > 100 mg/L 3
- d) Terrestrial toxicity : NOEC > 1000 mg/kg - 14 d
- e) Plant toxicity : NOEC > 1000 mg/kg - 14 d

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

DOT-UN Number: Not Applicable

ADR-UN number: Not Applicable

IATA-Un number: Not Applicable

IMDG-Un number: Not Applicable

UN proper shipping name

DOT-Proper Shipping Name: Not Applicable

ADR-Shipping Name: Not Applicable

IATA-Technical name: Not Applicable

IMDG-Technical name: Not Applicable

Transport hazard class(es)

DOT-Hazard Class: Not Applicable

ADR-Class: Not Applicable
IATA-Class: Not Applicable
IMDG-Class: Not Applicable

Packing group
DOT Packing Group: Not Applicable
ADR-Packing Group: Not Applicable
IATA-Packing group: Not Applicable
IMDG-Packing group: Not Applicable

Environmental hazards
Marine pollutant: No
Environmental Pollutant: Not Applicable
DOT-RQ: Yes DOT-RQ - Quantity: 5000 lbs

Transport in bulk according to IMO instruments

N.A.
Not Applicable

Special precautions

Department of Transportation (DOT):
Not Applicable
Road and Rail (ADR-RID) :
Not Applicable
Air (IATA) :
Not Applicable
Sea (IMDG) :
Not Applicable

15. REGULATORY INFORMATION

This Safety Data Sheet has been prepared according to the Hazard Communication Standard 2024 (HCS 2024)

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

calcium oxide; quicklime	is listed in TSCA	Section 8b
4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	is listed in TSCA	Section 8b Section 8a - PAIR Section 5
silica sand; quartz	is listed in TSCA	Section 8b
4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluene	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

Section 313 - Toxic chemical list:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	Reportable quantity:	5000	pounds
---	----------------------	------	--------

CAA - Clean Air Act

CAA listed substances:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	is listed in CAA	Section 112(b) - HAP Section 112(b) - HON
---	------------------	---

CWA - Clean Water Act

CWA listed substances:

No substances listed

California Proposition 65

silica sand; quartz	Listed as carcinogen
---------------------	----------------------

Substance(s) listed under Massachusetts Right to know:

calcium oxide; quicklime

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

silica sand; quartz

Substance(s) listed under Pennsylvania Right to know:

calcium oxide; quicklime

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

silica sand; quartz

Substance(s) listed under New Jersey Right to know:

calcium oxide; quicklime

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

silica sand; quartz

DSL - Domestic Substances List

All the substances are listed in the DSL.

This product complies with NDSL inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

Safety Data Sheet dated: 9/24/2025 - version 12

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.

Code	Hazard class and hazard category	Description
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A

A.4.1/1	Resp. Sens. 1	Respiratory Sensitization, Category 1
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EU CLP Index: Index number as reported in Annex VI to EU Reg. 1272/2008

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION