

Safety Data Sheet

PLANIBOND HI-MOD GEL / A

Safety Data Sheet dated: 09/15/2025 - version 9

Date of first edition: 11/25/2019



1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: PLANIBOND HI-MOD GEL / A

Trade code: 9019651

Recommended use of the chemical and restrictions on use

Recommended use: Epoxy adhesive

Restrictions on use: Not available

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Skin irritation, Category 2

Causes skin irritation.

Serious eye damage, Category 1

Causes serious eye damage.

Skin Sensitization, Category 1

May cause an allergic skin reaction.

Reproductive toxicity, Category 1B

May damage fertility. May damage the unborn child.

Acute aquatic hazard, category 2

Toxic to aquatic life

Chronic (long term) aquatic hazard, category 2

Toxic to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H360FD May damage fertility. May damage the unborn child.

H401 Toxic to aquatic life

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Call a POISON CENTER/ doctor/...

P310 Immediately call a doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with applicable regulations.

Hazards associated with foreseeable chemical reactions

None

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥40 - <50 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350
≥36 - <40 %	bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS:1675-54-3, 25085-99-8 EC:216-823-5 EU CLP Index:603-073-00-2	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2A, H319; Aquatic Chronic 2, H411; Aquatic Acute 2, H401
≥5 - <10 %	formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol;	CAS:9003-36-5 EC:701-263-0	Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Skin Sens. 1, H317
≥3 - <5 %	1,4-bis(2,3-epoxypropoxy)butane; butanedioldiglycidyl ether	CAS:2425-79-8 EC:219-371-7 EU CLP Index:603-072-00-7	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1, H317; Repr. 1B, H360; Aquatic Acute 3, H402

The actual concentration of the components listed above is withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.
OBTAIN IMMEDIATE MEDICAL ATTENTION.
Obtain medical attention if skin related symptoms persist.
Remove contaminated clothing immediately and dispose of safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.
Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
Hazardous combustion products: Not available
Explosive properties: Not Relevant
Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove persons to safety.
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Store cool and dry.
Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
silica sand; quartz CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m ³ A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA	Long Term: 0.15 mg/m ³
	ACGIH		Long Term: 0.025 mg/m ³ (R), A2 - Pulm fibrosis, lung cancer
	MAK	SWITZERLAND	Long Term: 0.15 mg/m ³
	EU		Long Term: 0.1 mg/m ³ Behaviour Binding

Predicted No Effect Concentration (PNEC) values

formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol;
CAS: 9003-36-5

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Fresh Water; PNEC Limit: 0.003 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0.294 mg/kg

Exposure Route: Marine water; PNEC Limit: 0.0003 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 0.0294 mg/kg

Exposure Route: Soil; PNEC Limit: 0.237 mg/kg

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and colour:	paste grey
Odour:	characteristic
Odour threshold:	Not Relevant
Melting point / freezing point:	Not Relevant
Initial boiling point and boiling range:	Not Relevant
Flammability:	Not Relevant
Upper/lower flammability or explosive limits:	Not Relevant
Flash point:	95 °C (203 °F)
Auto-ignition temperature:	Not Relevant
Decomposition temperature:	Not Relevant

pH:	7.00
Viscosity:	Not Relevant
Kinematic viscosity:	> 20,5 mm ² /sec (40 °C)
Solubility in water:	insoluble
Solubility in oil:	Not Relevant
Partition coefficient (n-octanol/water):	Not Relevant
Vapour pressure:	No data available
Evaporation rate:	Not Relevant
Relative density:	Not Relevant
Vapour density:	No data available

Particle characteristics:

Particle size:	No data available
----------------	-------------------

Other information

Explosive properties:	Not Relevant
Oxidizing properties:	Not Relevant
Solid/gas flammability:	Not Relevant
Substance Groups relevant properties:	Not Relevant
Miscibility:	Not Relevant
Fat Solubility:	Not Relevant
Conductivity:	Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

Stable

Chemical stability

Data not available.

Possibility of hazardous reactions

It may catch fire on contact with powerful oxidising agents.

Conditions to avoid

No data available

Incompatible materials

Data not available.

Hazardous decomposition products

Data not available.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	The product is classified: Serious eye damage, Category 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Reproductive toxicity, Category 1B(H360)

h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

silica sand; quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg LD50 Skin > 2000 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	a) acute toxicity	LD50 Skin Rabbit = 20 mg/kg LD50 Oral Rat = 11300 µL/kg
formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol;	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg LD50 Skin Rat > 2000 mg/kg
	i) STOT-repeated exposure	NOAEL Oral = 250 mg/kg
1,4-bis(2,3-epoxypropoxy)butane; butanedioldiglycidyl ether	a) acute toxicity	LD50 Oral Rat = 1134 mg/kg

Substance(s) listed on the IARC Monographs:

silica sand; quartz	Group 1
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Group 3

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 2(H401), Chronic (long term) aquatic hazard, category 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS: 1675-54-3, a) Aquatic acute toxicity : 25085-99-8 - EINECS: 216-823-5 - INDEX: 603-073-00-2	LC50 Fish = 2 mg/L 96h a) Aquatic acute toxicity : EC50 Daphnia = 1.8 mg/L 48h

formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol; CAS: 9003-36-5 a) Aquatic acute toxicity : LC50 Fish = 5.7 mg/L 96h
- EINECS: 701-263-0

a) Aquatic acute toxicity : EC50 Daphnia = 2.55 mg/L 48h

a) Aquatic acute toxicity : EC50 Algae = 1.8 mg/L 72h

1,4-bis(2,3-epoxypropoxy)butane; CAS: 2425-79-8 a) Aquatic acute toxicity : EC50 Fish = 19.8 mg/L 96h
butanedioldiglycidyl ether - EINECS: 219-371-7 - INDEX: 603-072-00-7

a) Aquatic acute toxicity : EC50 Daphnia = 75 mg/L 24h

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN3082

ADR-UN number: 3082

IATA-Un number: 3082

IMDG-Un number: 3082

UN proper shipping name

DOT-Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (epoxy resins)

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

Transport hazard class(es)

DOT-Hazard Class: 9

ADR-Class: 9

IATA-Class: 9

IMDG-Class: 9

Packing group

DOT Packing Group: III

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: No

Transport in bulk according to IMO instruments

N.A.

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 8, 146, 173, 335, IB3, T4, TP1, TP29

DOT-Label(s): 9

DOT-Symbol: N/A

DOT-Cargo Aircraft: N/A

DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A

DOT-Non-Bulk: N/A

DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID) :

ADR-Label: 9

ADR-Hazard identification number: 90

ADR-Transport category (Tunnel restriction code): 3 (-)

Air (IATA) :

IATA-Passenger Aircraft: 964

IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisioning: A97 A158 A197

Sea (IMDG) :

IMDG-Stowage and handling: Category A

IMDG-Segregation: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274 335 969

IMDG-EMS: F-A, S-F

15. REGULATORY INFORMATION

This Safety Data Sheet has been prepared according to the Hazard Communication Standard 2024 (HCS 2024)

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

silica sand; quartz is listed in TSCA Section 8b

bis-[4-(2,3-epoxipropoxy)phenyl]propane is listed in TSCA Section 8b

formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol; is listed in TSCA Section 8b

1,4-bis(2,3-epoxypropoxy)butane; is listed in TSCA Section 8b
butanedioldiglycidyl ether

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

silica sand; quartz Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

silica sand; quartz

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

silica sand; quartz

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

silica sand; quartz

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 9/15/2025 - version 9

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H350	May cause cancer.
H360	May damage fertility or the unborn child in contact with skin and if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4

A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.7/1B	Repr. 1B	Reproductive toxicity, Category 1B
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2
US-HAE/A3	Aquatic Acute 3	Acute aquatic hazard, category 3
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EU CLP Index: Index number as reported in Annex VI to EU Reg. 1272/2008

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 12. ECOLOGICAL INFORMATION