

Safety Data Sheet

KERAPOXY IEG CQ / B

Safety Data Sheet dated: 09/24/2025 - version 10

Date of first edition: 05/13/2015



1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: KERAPOXY IEG CQ / B

Trade code: 905UA9999

Recommended use of the chemical and restrictions on use

Recommended use: Hardener for epoxy products

Restrictions on use: Not available

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Acute toxicity (oral), Category 4

Skin corrosion, Category 1B

Serious eye damage, Category 1

Skin Sensitization, Category 1B

Reproductive toxicity, Category 2

Specific target organ toxicity following repeated exposure, Category 2

Acute aquatic hazard, category 2

Chronic (long term) aquatic hazard, category 2

Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility. Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated exposure if inhaled or swallowed.

Toxic to aquatic life

Toxic to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled or swallowed.

H401 Toxic to aquatic life

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P301+P312 IF SWALLOWED: Call a doctor if you feel unwell.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with applicable regulations.

Hazards associated with foreseeable chemical reactions

None

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥40 - <50 %	benzyl alcohol; benzenemethanol	CAS:100-51-6 EC:202-859-9 EU CLP Index:603-057-00-5	Acute Tox. 4, H302; Eye Irrit. 2A, H319
≥20 - <25 %	copolymer of benzenamine and formaldehyde, hydrogenated; polymeric cycloaliphatic amines	CAS:135108-88-2 EC:603-894-6	Acute Tox. 3, H301; Eye Dam. 1, H318; STOT RE 2, H373; Skin Corr. 1C, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412
≥10 - <15 %	formaldehyde, polymer with 1,3-benzenedimethanamine and phenol; Reaction mass of benzyl alcohol and m-phenylenebis(methylamine) and Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS:57214-10-5 EC:500-137-0	Skin Corr. 1B, H314; Skin Sens. 1, H317
≥10 - <15 %	1,3-benzenedimethanamine; m-phenylenebis(methylamine)	CAS:1477-55-0 EC:216-032-5	Acute Tox. 4, H332; Acute Tox. 4, H302; Aquatic Chronic 3, H412; Aquatic Acute 3, H402; Skin Corr. 1B, H314; Skin Sens. 1B, H317
≥3 - <5 %	reaction mass of 4,4'-Isopropylidenediphenol, 1-chloro-2,3-epoxypropane and ethylenediamine	CAS:72480-18-3 EC:701-405-1	Acute Tox. 4, H302; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410
≥2.5 - <3 %	tetraethylenepentamine; 3,6,9-triazaundecamethylenediamine	CAS:112-57-2 EC:203-986-2 EU CLP Index:612-060-	Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312

≥2.5 - <3 % 4-nonylphenol, branched; Isononylphenol

CAS:84852-15-3
EC:284-325-5
EU CLP Index:601-053-00-8Repr. 2, H361fd; Skin Corr. 1B, H314;
Aquatic Acute 1, H400; Aquatic Chronic 1,
H410; Acute Tox. 4, H302

The actual concentration of the components listed above is withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Give nothing to eat or drink.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: Not available
- Explosive properties: Not available
- Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Provide adequate ventilation.
- Use appropriate respiratory protection.
- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Exercise the greatest care when handling or opening the container.
- Use localized ventilation system.
- Don't use empty container before they have been cleaned.
- Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
- Contaminated clothing should be changed before entering eating areas.
- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
benzyl alcohol; benzenemethanol CAS: 100-51-6	MAK	GERMANY	Long Term: 22 mg/m3 - 5 ppm
	MAK	SWITZERLAND	Long Term: 22 mg/m3 - 5 ppm
1,3-benzenedimethanamine; m-phenylenebis(methylamine) CAS: 1477-55-0	ACGIH		Short Term: Ceiling - 0,1 mg/m3 Skin - Eye, skin, and GI irr
	ACGIH		Short Term: Ceiling - 0,1 mg/m3
	ACGIH		Skin - potential significant contribution to overall exposure by the cutaneous route;eye, gastrointestinal and skin irritation
	MAK	AUSTRIA	Long Term: 0,1 mg/m3; Short Term: 0,1 mg/m3
	MAK	SWITZERLAND	Long Term: 0,1 mg/m3
	MAK	AUSTRIA	Short Term: Ceiling - 0,1 mg/m3
	ACGIH		Short Term: Ceiling - 0,1 mg/m3
	ACGIH		Skin - potential significant contribution to overall exposure by the cutaneous route;eye, gastrointestinal and skin irritation
	ACGIH		Short Term: Ceiling - 0,018 ppm

Predicted No Effect Concentration (PNEC) values

- copolymer of benzenamine and formaldehyde, hydrogenated; polymeric cycloaliphatic amines
CAS: 135108-88-2
Exposure Route: Marine water sediments; PNEC Limit: 1,5 mg/kg
- Exposure Route: Soil; PNEC Limit: 1,8 mg/kg
- Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1,9 mg/l
- Exposure Route: Freshwater sediments; PNEC Limit: 15 mg/kg
- Exposure Route: Fresh Water; PNEC Limit: 0,015 mg/l

Exposure Route: Marine water; PNEC Limit: 0,002 mg/l

1,3-benzenedimethanamine;
m-phenylenebis
(methylamine)
CAS: 1477-55-0

Exposure Route: Marine water; PNEC Limit: 0,0094 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0,43 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0,043 mg/kg

Exposure Route: Intermittent release; PNEC Limit: 0,152 mg/l

Exposure Route: Soil; PNEC Limit: 0,045 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

tetraethylenepentamine;
3,6,9-triazaundecamethylenedia
mine
CAS: 112-57-2

Exposure Route: Marine water; PNEC Limit: 0,00068 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 3,34 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0,343 mg/kg

Exposure Route: Soil; PNEC Limit: 0,683 mg/kg

4-nonylphenol, branched;
Isononylphenol
CAS: 84852-15-3

Exposure Route: Marine water; PNEC Limit: 0,000527 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 4,62 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 1,23 mg/kg

Derived No Effect Level (DNEL) values

copolymer of
benzenamine and
formaldehyde,
hydrogenated; polymeric
cycloaliphatic amines
CAS: 135108-88-2

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 2 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 2 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 0,2 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Industry: 6 mg/kg

1,3-benzenedimethanamine;
m-phenylenebis
(methylamine)
CAS: 1477-55-0

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 0,33 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 1,2 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 0,2 mg/m³

tetraethylenepentamine;
3,6,9-triazaundecamethylenedia
mine
CAS: 112-57-2

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Consumer: 10 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 0,74 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Consumer: 0,32 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0,53 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 0,00129 mg/l

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 0,00038 mg/l

4-nonylphenol, branched; Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Isononylphenol
CAS: 84852-15-3
Worker Industry: 0,5 mg/m³; Consumer: 0,4 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 1 mg/m³; Consumer: 0,8 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 7,5 mg/kg; Consumer: 3,8 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Industry: 15 mg/kg; Consumer: 7,6 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0,08 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 0,4 mg/kg

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Nitrile rubber - NBR: thickness $\geq 0,35$ mm; breakthrough time ≥ 480 min.

Butyl rubber - IIR: thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Fluorinated rubber - FKM: thickness $\geq 0,4$ mm; breakthrough time ≥ 480 min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and colour:	viscous liquid amber
Odour:	DXZH00044
Odour threshold:	No data available
Melting point / freezing point:	No data available
Initial boiling point and boiling range:	100 °C (212 °F)
Flammability:	No data available
Upper/lower flammability or explosive limits:	No data available
Flash point:	94 °C (201 °F)
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available

pH:	No data available
Viscosity:	No data available
Kinematic viscosity:	> 20,5 mm ² /sec (40 °C)
Solubility in water:	insoluble
Solubility in oil:	No data available
Partition coefficient (n-octanol/water):	No data available
Vapour pressure:	No data available
Evaporation rate:	No data available
Relative density:	1.06 g/cm ³
Vapour density:	No data available

Particle characteristics:

Particle size:	No data available
----------------	-------------------

Other information

Explosive properties:	No data available
Oxidizing properties:	No data available
Solid/gas flammability:	No data available
Substance Groups relevant properties:	No data available
Miscibility:	No data available
Fat Solubility:	No data available
Conductivity:	No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	The product is classified: Acute toxicity (oral), Category 4(H302) ATEmix - Oral : 796.183 mg/kg bw
b) skin corrosion/irritation	The product is classified: Skin corrosion, Category 1B(H314)
c) serious eye damage/irritation	The product is classified: Serious eye damage, Category 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1B(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Reproductive toxicity, Category 2(H361)

h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	The product is classified: Specific target organ toxicity following repeated exposure, Category 2(H373)
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

benzyl alcohol; benzenemethanol	a) acute toxicity	LD50 Oral Rat = 1620, mg/kg
copolymer of benzenamine and formaldehyde, hydrogenated; polymeric cycloaliphatic amines	a) acute toxicity	LD50 Oral Rat = 300, mg/kg bw LD50 Skin Rabbit > 2000, mg/kg bw
1,3- benzenedimethanamine; m- phenylenebis (methylaniline)	a) acute toxicity	LD50 Oral Mouse = 930 mg/kg LD50 Skin Rabbit = 2000 mg/kg LC50 Inhalation Mist Rat = 1,34 mg/l 4h LC50 Inhalation Rat = 700, ppm 1h
reaction mass of 4,4'- Isopropylidenediphenol, 1-chloro-2,3- epoxypropane and ethylenediamine	a) acute toxicity	LD50 Oral Rat > 200, mg/kg LD50 Oral Rabbit = 10000, mg/kg
4-nonylphenol, branched; Isononylphenol	a) acute toxicity	LD50 Oral Rat = 1246, mg/kg

Substance(s) listed on the IARC Monographs:

None

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 2(H401), Chronic (long term) aquatic hazard, category 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
-----------	--------------	-------------

benzyl alcohol; benzenemethanol	CAS: 100-51-6 - EINECS: 202-859-9 - INDEX: 603-057-00-5	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 460 mg/L 96h EPA
copolymer of benzenamine and formaldehyde, hydrogenated; polymeric cycloaliphatic amines	CAS: 135108-88-2 - EINECS: 603-894-6	a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 63 mg/L 96h ECHA a) Aquatic acute toxicity : EC50 Daphnia = 15,4 mg/L 48h a) Aquatic acute toxicity : EC50 Algae = 43,94 mg/L 72h
formaldehyde, polymer with 1,3-benzenedimethanamine and phenol; Reaction mass of benzyl alcohol and m-phenylenebis(methylamine) and Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS: 57214-10-5 - EINECS: 500-137-0	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 25,9 mg/L 96h ECHA
1,3-benzenedimethanamine; m-phenylenebis(methylamine)	CAS: 1477-55-0 - EINECS: 216-032-5	a) Aquatic acute toxicity : EC50 Algae = 20 mg/L 72h a) Aquatic acute toxicity : EC50 Daphnia = 15,2 mg/L 48h a) Aquatic acute toxicity : LC50 Fish Oryzias latipes = 87,6 mg/L 96h ECHA
reaction mass of 4,4'-Isopropylidenediphenol, 1-chloro-2,3-epoxypropane and ethylenediamine	CAS: 72480-18-3 - EINECS: 701-405-1	a) Aquatic acute toxicity : NOEC Fish = 160 µg/L 96h a) Aquatic acute toxicity : LL50 Fish = 160 µg/L 96h a) Aquatic acute toxicity : EL50 Daphnia = 1,7 mg/L 48h a) Aquatic acute toxicity : NOELR Daphnia = 1 mg/L 48h a) Aquatic acute toxicity : EL50 Algae > 160 µg/L 72h
tetraethylenepentamine; 3,6,9-triazaundecamethylenediamine	CAS: 112-57-2 - EINECS: 203-986-2 - INDEX: 612-060-00-0	a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 420 mg/L 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 24,1 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 2,1 mg/L 72h IUCLID
4-nonylphenol, branched; Isononylphenol	CAS: 84852-15-3 - EINECS: 284-325-5 - INDEX: 601-053-00-8	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 0,135 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 0,1351 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 0,14 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 0,36 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 0,16 mg/L 72h EPA b) Aquatic chronic toxicity : NOEC Fish 0,009 mg/L 21d ECHA

Persistence and degradability

Component

copolymer of benzenamine and formaldehyde, hydrogenated; polymeric cycloaliphatic amines

Persitence/Degradability:

Non-readily biodegradable

Bioaccumulative potential

Component	Bioaccumulation	Test	Duration	Value
4-nonylphenol, branched; Isononylphenol	Not bioaccumulative	BCF - Bioconcentration factor	28 d	740
Mobility in soil				
N.A.				
Other adverse effects				
N.A.				

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN2735

ADR-UN number: 2735

IATA-Un number: 2735

IMDG-Un number: 2735

UN proper shipping name

DOT-Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (m-xylylendiamine - nonylphenol mixture)

ADR-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (m-xylylendiamine - nonylphenol mixture)

IATA-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. (m-xylylendiamine - nonylphenol mixture)

IMDG-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. (m-xylylendiamine - nonylphenol mixture)

Transport hazard class(es)

DOT-Hazard Class: 8

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

Packing group

DOT Packing Group: II

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: No

Transport in bulk according to IMO instruments

N.A.

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): B2, IB2, T11, TP1, TP27

DOT-Label(s): 8

DOT-Symbol: N/A
DOT-Cargo Aircraft: 30 L
DOT-Passenger Aircraft: 1 L
DOT-Bulk: 242
DOT-Non-Bulk: 202
DOT-Limited Quantity threshold: 1 L
Road and Rail (ADR-RID) :
ADR-Label: 8
ADR-Hazard identification number: 80
ADR-Transport category (Tunnel restriction code): 2 (E)
Air (IATA) :
IATA-Passenger Aircraft: 851
IATA-Cargo Aircraft: 855
IATA-Label: 8
IATA-Subsidiary hazards: -
IATA-Erg: 8L
IATA-Special Provisioning: A3 A803
Sea (IMDG) :
IMDG-Stowage and handling: Category A
IMDG-Segregation: SG35 SGG18
IMDG-Subsidiary hazards: -
IMDG-Special Provisioning: 274
IMDG-EMS: F-A, S-B

15. REGULATORY INFORMATION

This Safety Data Sheet has been prepared according to the Hazard Communication Standard 2024 (HCS 2024)

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

benzyl alcohol; benzenemethanol is listed in TSCA Section 8b

copolymer of benzenamine and formaldehyde, hydrogenated; polymeric cycloaliphatic amines is listed in TSCA Section 8b

formaldehyde, polymer with 1,3-benzenedimethanamine and phenol; Reaction mass of benzyl alcohol and m-phenylenebis(methylamine) and Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol is listed in TSCA Section 8b

1,3-benzenedimethanamine; m-phenylenebis(methylamine) is listed in TSCA Section 8b

reaction mass of 4,4'-Isopropylidenediphenol, 1-chloro-2,3-epoxypropane and ethylenediamine is listed in TSCA Section 8b

tetraethylenepentamine; 3,6,9-triazaundecamethylenediamine is listed in TSCA Section 8b

4-nonylphenol, branched; Isononylphenol is listed in TSCA Section 8b Section 8a - PAIR Section 5a - SNUR Section 12b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

4-nonylphenol, branched; Isononylphenol

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act**CAA listed substances:**

benzyl alcohol; benzenemethanol is listed in CAA Section 112(b) - HON
tetraethylenepentamine; 3,6,9-triazaundecamethylenediamine is listed in CAA Section 112(b) - HON

CWA - Clean Water Act**CWA listed substances:**

No substances listed

USA - State specific regulations**California Proposition 65****Substance(s) listed under California Proposition 65:**

No substances listed

Massachusetts Right to know**Substance(s) listed under Massachusetts Right to know:**

benzyl alcohol; benzenemethanol
1,3-benzenedimethanamine; m-phenylenebis(methylamine)
tetraethylenepentamine; 3,6,9-triazaundecamethylenediamine

Pennsylvania Right to know**Substance(s) listed under Pennsylvania Right to know:**

benzyl alcohol; benzenemethanol
1,3-benzenedimethanamine; m-phenylenebis(methylamine)
tetraethylenepentamine; 3,6,9-triazaundecamethylenediamine

New Jersey Right to know**Substance(s) listed under New Jersey Right to know:**

1,3-benzenedimethanamine; m-phenylenebis(methylamine)
tetraethylenepentamine; 3,6,9-triazaundecamethylenediamine

Canada - Federal regulations**DSL - Domestic Substances List**

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory**NPRI (National Pollutant Release Inventory) - List of substances listed.**

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 9/24/2025 - version 10

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/3/Oral	Acute Tox. 3	Acute toxicity (oral), Category 3
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
A.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.7/2	Repr. 2	Reproductive toxicity, Category 2
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
US-HAE/A3	Aquatic Acute 3	Acute aquatic hazard, category 3
US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
US-HAE/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 IMDG: International Maritime Code for Dangerous Goods.
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 CLP: Classification, Labeling, Packaging.
 EU CLP Index: Index number as reported in Annex VI to EU Reg. 1272/2008
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 INCI: International Nomenclature of Cosmetic Ingredients.
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 DNEL: Derived No Effect Level.
 PNEC: Predicted No Effect Concentration.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 WGK: German Water Hazard Class.
 KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION

- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION