

Safety Data Sheet

MAPECOAT TNS BASE COAT ULTRA NA

Safety Data Sheet dated: 09/24/2025 - version 4

Date of first edition: 09/06/2022



1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: MAPECOAT TNS BASE COAT ULTRA NA

Trade code: 9062508

Recommended use of the chemical and restrictions on use

Recommended use: Paint

Restrictions on use: Not available

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Skin Sensitization, Category 1B

May cause an allergic skin reaction.

Acute aquatic hazard, category 3

Harmful to aquatic life

Chronic (long term) aquatic hazard, category 3

Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Warning

Hazard statements

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

Hazards associated with foreseeable chemical reactions

None

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥10 - <15 %	rubber, reclaimed	CAS:139497-04-4 EC:639-441-4	Aquatic Chronic 3, H412
≥10 - <15 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350
≥5 - <10 %	carbon black; acetylene black	CAS:1333-86-4 EC:215-609-9	Comb. Dust, USH003
≥1 - <2.5 %	acetone; propan-2-one	CAS:67-64-1 EC:200-662-2 EU CLP Index:606-001-00-8	Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336
≥1 - <2.5 %	poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(methylphenyl)-.omega.-hydroxy-; Cresol propoxylate	CAS:9064-13-5 EC:618-605-9	Skin Sens. 1B, H317
≥0.2 - <0.25 %	polyoxyl 10 oleyl ether; (Z)-9-Octadecen-1-ol ethoxylated	CAS:9004-98-2 EC:500-016-2	Skin Irrit. 2, H315; Aquatic Acute 1, H400
≥0.2 - <0.25 %	n-1,3-dimethylbutyl-n'-phenyl-p-phenylenediamine ; 1,4-Benzenediamine, N1-(1,3-dimethylbutyl)-N4-phenyl-	CAS:793-24-8 EC:212-344-0	Acute Tox. 4, H302; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317

The actual concentration of the components listed above is withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

- Wash immediately with water.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Not available

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

- (see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
silica sand; quartz CAS: 14808-60-7	ACGIH		Long Term: 0,025 mg/m ³ A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA	Long Term: 0,15 mg/m ³
	ACGIH		Long Term: 0,025 mg/m ³ (R), A2 - Pulm fibrosis, lung cancer
	MAK	SWITZERLAND	Long Term: 0,15 mg/m ³
		D	
	EU		Long Term: 0,1 mg/m ³ Behaviour Binding
carbon black; acetylene black OSHA			Long Term: 3,5 mg/m ³

CAS: 1333-86-4

acetone; propan-2-one CAS: 67-64-1	ACGIH		Long Term: 3 mg/m3 A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;bronchitis;
	ACGIH		Long Term: 3 mg/m3 A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;bronchitis
	ACGIH		Long Term: 250 ppm; Short Term: 500 ppm A4, BEI - URT and eye irr, CNS impair
	MAK	GERMANY	Long Term: 1200 mg/m3 - 500 ppm
	OSHA		Long Term: 2400 mg/m3 - 1000 ppm
	ACGIH		Long Term: 250 ppm; Short Term: 500 ppm A4 - Not Classifiable as a Human Carcinogen;CNS impairment;eye and upper respiratory tract irritation
	MAK	AUSTRIA	Long Term: 1200 mg/m3 - 500 ppm; Short Term: 4800 mg/m3 - 2000 ppm
	MAK	SWITZERLAND	Long Term: 1200 mg/m3 - 500 ppm
	EU		Long Term: 1210 mg/m3 - 500 ppm
	MAK	GERMANY	Long Term: 2 mg/m3
n-1,3-dimethylbutyl-n'-phenyl-p-phenylenediamine ; 1,4-Benzenediamine, N1-(1,3-dimethylbutyl)-N4-phenyl- CAS: 793-24-8	MAK	SWITZERLAND	Long Term: 3 mg/m3

Biological limit values

acetone; propan-2-one
CAS: 67-64-1

Biological Indicator: Acetone; Sampling Period: End of turn
Value: 25 mg/L; Medium: Urine
Remark: Not Specific

Predicted No Effect Concentration (PNEC) values

acetone; propan-2-one
CAS: 67-64-1

Exposure Route: Freshwater sediments; PNEC Limit: 30,4 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 3,04 mg/kg

Exposure Route: Fresh Water; PNEC Limit: 10,6 mg/l

Exposure Route: Marine water; PNEC Limit: 1,06 mg/l

Exposure Route: Soil; PNEC Limit: 29,5 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

Derived No Effect Level (DNEL) values

acetone; propan-2-one
CAS: 67-64-1

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 186 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 2420 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 1210 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 62 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 62 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 200 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Industry: 2420 mg/m3

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:
Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and colour:	viscous liquid black or grey
Odour:	ammonia
Odour threshold:	Not Relevant
Melting point / freezing point:	Not Relevant
Initial boiling point and boiling range:	Not Relevant
Flammability:	Not Relevant
Upper/lower flammability or explosive limits:	Not Relevant
Flash point:	100 °C (212 °F)
Auto-ignition temperature:	Not Relevant
Decomposition temperature:	Not Relevant
pH:	8.50
Viscosity:	Not Relevant
Kinematic viscosity:	No data available
Solubility in water:	easily soluble
Solubility in oil:	insoluble
Partition coefficient (n-octanol/water):	Not Relevant
Vapour pressure:	Not Relevant
Evaporation rate:	Not Relevant
Relative density:	1.10 g/cm ³
Vapour density:	Not Relevant

Particle characteristics:

Particle size:	No data available
----------------	-------------------

Other information

Explosive properties:	Not Relevant
Oxidizing properties:	Not Relevant
Solid/gas flammability:	Not Relevant
Substance Groups relevant properties:	Not Relevant
Miscibility:	Not Relevant

Fat Solubility:	Not Relevant
Conductivity:	Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified
	Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1B(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

silica sand; quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg LD50 Skin > 2000 mg/kg
carbon black; acetylene black	a) acute toxicity	LD50 Oral Rat > 8000 mg/kg LD50 Oral Rat > 15400 mg/kg
acetone; propan-2-one	a) acute toxicity	LD50 Oral Rat = 5800 mg/kg LD50 Skin Rabbit = 20000 mg/kg LC50 Inhalation Rat = 76 mg/l 4h LC50 Inhalation Rat = 50100, mg/m3 8h
polyoxyl 10 oleyl ether; (Z)-9-Octadecen-1-ol	a) acute toxicity	LD50 Oral Rat 2700 mg/kg

ethoxylated

LD50 Oral Rat = 2700 mg/kg

n-1,3-dimethylbutyl-n'-phenyl-p-phenylenediamine ; 1,4-Benzenediamine, N1-(1,3-dimethylbutyl)-N4-phenyl-

LD50 Skin Rabbit > 7940 mg/kg

LD50 Oral Rat = 3580 mg/kg

Substance(s) listed on the IARC Monographs:

- silica sand; quartz Group 1
- carbon black; acetylene black Group 2B

Substance(s) listed as OSHA Carcinogen(s):

- silica sand; quartz
- carbon black; acetylene black

Substance(s) listed as NIOSH Carcinogen(s):

- silica sand; quartz
- carbon black; acetylene black

Substance(s) listed on the NTP report on Carcinogens:

- silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.
Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402), Chronic (long term) aquatic hazard, category 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
carbon black; acetylene black	CAS: 1333-86-4 - EINECS: 215-609-9	a) Aquatic acute toxicity : LC50 Fish > 1000 mg/L 96
		a) Aquatic acute toxicity : EC50 Daphnia > 5600 mg/L 24
		a) Aquatic acute toxicity : EC50 Algae > 10000 mg/L 72
acetone; propan-2-one	CAS: 67-64-1 - EINECS: 200-662-2 - INDEX: 606-001-00-8	a) Aquatic acute toxicity : EC50 Daphnia = 8800 mg/L 48h
		a) Aquatic acute toxicity : LC50 Fish = 5540 mg/L 96h
		a) Aquatic acute toxicity : EC50 Algae = 302 mg/L 96h
n-1,3-dimethylbutyl-n'-phenyl-p-phenylenediamine ; 1,4-Benzenediamine, N1-(1,3-dimethylbutyl)-N4-phenyl-	CAS: 793-24-8 - EINECS: 212-344-0	a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 0,4 mg/L 96h IUCLID
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 0,51 mg/L 48h IUCLID
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 0,6 mg/L 96h IUCLID

Persistence and degradability

Component	Persitence/Degradability:
acetone; propan-2-one	Readily biodegradable

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

DOT-UN Number: Not Applicable

ADR-UN number: Not Applicable

IATA-Un number: Not Applicable

IMDG-Un number: Not Applicable

UN proper shipping name

DOT-Proper Shipping Name: Not Applicable

ADR-Shipping Name: Not Applicable

IATA-Technical name: Not Applicable

IMDG-Technical name: Not Applicable

Transport hazard class(es)

DOT-Hazard Class: Not Applicable

ADR-Class: Not Applicable

IATA-Class: Not Applicable

IMDG-Class: Not Applicable

Packing group

DOT Packing Group: Not Applicable

ADR-Packing Group: Not Applicable

IATA-Packing group: Not Applicable

IMDG-Packing group: Not Applicable

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: Yes DOT-RQ - Quantity: 5000 lbs

Transport in bulk according to IMO instruments

N.A.

Not Applicable

Special precautions

Department of Transportation (DOT):

Not Applicable

Road and Rail (ADR-RID) :

Not Applicable
Air (IATA) :
Not Applicable
Sea (IMDG) :
Not Applicable

15. REGULATORY INFORMATION

This Safety Data Sheet has been prepared according to the Hazard Communication Standard 2024 (HCS 2024)

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

rubber, reclaimed is listed in TSCA Section 8b
silica sand; quartz is listed in TSCA Section 8b
carbon black; acetylene black is listed in TSCA Section 8b
acetone; propan-2-one is listed in TSCA Section 8b
poly[oxy(methyl-1,2-ethanediyl)], is listed in TSCA Section 8b
.alpha.-(methylphenyl)-.omega.-hydroxy-; Cresol propoxylate

polyoxyl 10 oleyl ether; (Z)-9-Octadecen-1-ol ethoxylated is listed in TSCA Section 8b

n-1,3-dimethylbutyl-n'-phenyl-p-phenylenediamine ; 1,4-Benzenediamine, N1-(1,3-dimethylbutyl)-N4-phenyl- is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

acetone; propan-2-one

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

acetone; propan-2-one Reportable quantity: 5000 pounds

CAA - Clean Air Act

CAA listed substances:

acetone; propan-2-one is listed in CAA Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

silica sand; quartz Listed as carcinogen
carbon black; acetylene black Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

silica sand; quartz
carbon black; acetylene black
acetone; propan-2-one

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

silica sand; quartz
carbon black; acetylene black
acetone; propan-2-one

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

silica sand; quartz
carbon black; acetylene black
acetone; propan-2-one

Canada - Federal regulations

DSL - Domestic Substances List

Not compliant to DSL inventory

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 9/24/2025 - version 4

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
USH003	May form combustible dust concentrations in air.

Code	Hazard class and hazard category	Description
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
B.6/2	Flam. Liq. 2	Flammable Liquids — Category 2
US-ADD/CD	Comb. Dust	Combustible dust
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
US-HAE/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
CLP: Classification, Labeling, Packaging.
EU CLP Index: Index number as reported in Annex VI to EU Reg. 1272/2008
EINECS: European Inventory of Existing Commercial Chemical Substances.
INCI: International Nomenclature of Cosmetic Ingredients.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
GefStoffVO: Ordinance on Hazardous Substances, Germany.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
DNEL: Derived No Effect Level.
PNEC: Predicted No Effect Concentration.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.
KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 16. OTHER INFORMATION