

Safety Data Sheet

ULTRABOND TRACK PU 2K / A

Safety Data Sheet dated: 09/24/2025 - version 16

Date of first edition: 05/14/2015



1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: ULTRABOND TRACK PU 2K / A

Trade code: 906UX9990

Recommended use of the chemical and restrictions on use

Recommended use: Epoxy/ Polyurethane Adhesive

Restrictions on use: Not available

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flammable Liquids — Category 3

Eye irritation, Category 2A

Skin Sensitization, Category 1

Reproductive toxicity, Category 2

Acute aquatic hazard, category 3

Chronic (long term) aquatic hazard, category 3

Flammable liquid and vapour.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility. Suspected of damaging the unborn child.

Harmful to aquatic life

Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Warning

Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

- P243

Take action to prevent static discharge.
- P260

Do not breathe mist/vapours/spray.
- P264

Wash skin thoroughly after handling.
- P273

Avoid release to the environment.
- P280

Wear protective gloves/clothing and eye/face protection.
- P302+P352

IF ON SKIN: Wash with plenty of water.
- P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313

IF exposed or concerned: Get medical advice/attention.
- P314

Get medical advice/attention if you feel unwell.
- P333+P313

If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313

If eye irritation persists: Get medical advice/attention.
- P362+P364

Take off contaminated clothing and wash it before reuse.
- P370+P378

In case of fire, use a dry powder fire extinguisher to extinguish.
- P403+P235

Store in a well-ventilated place. Keep cool.
- P501

Dispose of contents/container in accordance with applicable regulations.

Hazards associated with foreseeable chemical reactions

None

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥5 - <10 %	bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS:1675-54-3, 25085-99-8 EC:216-823-5 EU CLP Index:603-073-00-2	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2A, H319; Aquatic Chronic 2, H411; Aquatic Acute 2, H401
≥3 - <5 %	ethylacetate; acetic acid ethyl ester	CAS:141-78-6 EC:205-500-4 EU CLP Index:607-022-00-5	Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336
≥1 - <2.5 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350
≥0.6 - <1 %	4-nonylphenol, branched; Isononylphenol	CAS:84852-15-3 EC:284-325-5 EU CLP Index:601-053-00-8	Repr. 2, H361fd; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302

The actual concentration of the components listed above is withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.
OBTAIN IMMEDIATE MEDICAL ATTENTION.
Obtain medical attention if skin related symptoms persist.
Remove contaminated clothing immediately and dispose of safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Data not available.

Always keep in a well ventilated place.
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
 Store in a well-ventilated place. Keep cool.
 Avoid direct exposure to sunlight.
 Opened containers must be carefully resealed and kept upright to prevent leakage.
 Flammable mixtures may accumulate within the headspace of containers at room temperature.
 Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.
 Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.
 Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Electrical installations / working materials must comply with the technological safety standards.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
ethylacetate; acetic acid ethyl ester CAS: 141-78-6	ACGIH		Long Term: 540 mg/m ³
	MAK		Long Term: 1400 mg/m ³
	OSHA	AUSTRALIA	Short Term: Ceiling - 1440 mg/m ³ - 400 ppm
	ACGIH		Long Term: 720 mg/m ³ - 400 ppm
	MAK	AUSTRIA	Short Term: 1468 mg/m ³
	MAK	SWITZERLAND	Long Term: 730 mg/m ³ - 200 ppm; Short Term: 1460 mg/m ³ - 400 ppm
silica sand; quartz CAS: 14808-60-7	EU		Long Term: 734 mg/m ³ - 200 ppm; Short Term: 1468 mg/m ³ - 400 ppm
	ACGIH		Long Term: 0,025 mg/m ³ A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA	Long Term: 0,15 mg/m ³
	ACGIH		Long Term: 0,025 mg/m ³ (R), A2 - Pulm fibrosis, lung cancer
	MAK	SWITZERLAND	Long Term: 0,15 mg/m ³
	EU		Long Term: 0,1 mg/m ³ Behaviour Binding

Predicted No Effect Concentration (PNEC) values

ethylacetate; acetic acid ethyl ester CAS: 141-78-6	Exposure Route: Fresh Water; PNEC Limit: 0,26 mg/l Remark: PNEC
	Exposure Route: Marine water; PNEC Limit: 0,026 mg/l Remark: PNEC
	Exposure Route: Intermittent release; PNEC Limit: 1,65 mg/l Remark: PNEC
	Exposure Route: Freshwater sediments; PNEC Limit: 1,25 mg/kg Remark: PNEC
	Exposure Route: Marine water sediments; PNEC Limit: 0,125 mg/kg

Remark: PNEC

Exposure Route: Soil; PNEC Limit: 0,24 mg/kg
Remark: PNEC

Exposure Route: Oral; PNEC Limit: 200 mg/kg
Remark: PNEC

4-nonylphenol, branched; Exposure Route: Fresh Water; PNEC Limit: 0,000614 mg/l
Isononylphenol
CAS: 84852-15-3

Exposure Route: Marine water; PNEC Limit: 0,000527 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 4,62 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 1,23 mg/kg

Derived No Effect Level (DNEL) values

ethylacetate; acetic acid ethyl ester
CAS: 141-78-6
Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 1468 mg/m3
Remark: DNEL

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 4,5 mg/kg
Remark: DNEL

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Consumer: 367 mg/m3
Remark: DNEL

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 1468 mg/m3
Remark: DNEL

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 63 mg/kg
Remark: DNEL

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 734 mg/m3
Remark: DNEL

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 734 mg/m3
Remark: DNEL

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Consumer: 734 mg/m3
Remark: DNEL

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Consumer: 734 mg/m3
Remark: DNEL

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 37 mg/kg
Remark: DNEL

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 367 mg/m3
Remark: DNEL

4-nonylphenol, branched; Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Isononylphenol
CAS: 84852-15-3
Worker Industry: 0,5 mg/m3; Consumer: 0,4 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 1 mg/m3; Consumer: 0,8 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 7,5 mg/kg; Consumer: 3,8 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Industry: 15 mg/kg; Consumer: 7,6 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0,08 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects

Consumer: 0,4 mg/kg

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and colour:	paste various
Odour:	characteristic
Odour threshold:	Not Relevant
Melting point / freezing point:	Not Relevant
Initial boiling point and boiling range:	Not Relevant
Flammability:	Not Relevant
Upper/lower flammability or explosive limits:	Not Relevant
Flash point:	40 °C (104 °F)
Auto-ignition temperature:	Not Relevant
Decomposition temperature:	Not Relevant
pH:	Not Relevant
Viscosity:	700,000.00 mPA-s
Kinematic viscosity:	> 20,5 mm ² /sec (40 °C)
Solubility in water:	insoluble
Solubility in oil:	partly soluble
Partition coefficient (n-octanol/water):	Not Relevant
Vapour pressure:	Not Relevant
Evaporation rate:	Not Relevant
Relative density:	1.46 g/cm ³
Vapour density:	Not Relevant

Particle characteristics:

Particle size:	No data available
----------------	-------------------

Other information

Explosive properties:	Not Relevant
-----------------------	--------------

Oxidizing properties:	Not Relevant
-----------------------	--------------

Solid/gas flammability:	Data not available.
Substance Groups relevant properties:	Not Relevant
Miscibility:	Not Relevant
Fat Solubility:	Not Relevant
Conductivity:	Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

No data available

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

No data available

Avoid accumulating electrostatic charge.

Incompatible materials

Data not available.

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

Data not available.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Reproductive toxicity, Category 2(H361)
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

bis-[4-(2,3-epoxipropoxy)phenyl]propane	a) acute toxicity	LD50 Skin Rabbit = 20 mg/kg
		LD50 Oral Rat = 11300 µL/kg
ethylacetate; acetic acid ethyl ester	a) acute toxicity	LC50 Inhalation Rat = 1600 mg/l
		LD50 Oral Rabbit = 4935 mg/kg
		LD50 Oral Rat = 11,3 g/kg

LD50 Skin Rabbit > 20000 mg/kg
LD50 Oral Mouse = 4100 mg/kg
LC50 Inhalation Rat = 4000, ppm 4h

silica sand; quartz a) acute toxicity LD50 Oral > 2000 mg/kg
LD50 Skin > 2000 mg/kg

4-nonylphenol, branched; a) acute toxicity LD50 Oral Rat = 1246, mg/kg
Isononylphenol

Substance(s) listed on the IARC Monographs:

bis-[4-(2,3-epoxipropoxy)phenyl]propane Group 3

silica sand; quartz Group 1

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402), Chronic (long term) aquatic hazard, category 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS: 1675-54-3, a) Aquatic acute toxicity : 25085-99-8 - EINECS: 216-823-5 - INDEX: 603-073-00-2	LC50 Fish = 2 mg/L 96h
ethylacetate; acetic acid ethyl ester	CAS: 141-78-6 - EINECS: 205-500-4 - INDEX: 607-022-00-5	a) Aquatic acute toxicity : EC50 Daphnia = 1,8 mg/L 48h a) Aquatic acute toxicity : LC50 Algae = 3300 mg/L 48
4-nonylphenol, branched; Isononylphenol	CAS: 84852-15-3 - EINECS: 284-325-5 - INDEX: 601-053-00-8	a) Aquatic acute toxicity : LC50 Fish = 230 mg/L 96 b) Aquatic chronic toxicity : LC50 Algae = 5600 mg/L 48 a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 220 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 484 mg/L 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 560 mg/L 48h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 0,135 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 0,1351 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 0,14 mg/L 48h IUCLID

a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 0,36 mg/L 96h EPA

a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 0,16 mg/L 72h EPA

b) Aquatic chronic toxicity : NOEC Fish 0,009 mg/L 21d ECHA

Persistence and degradability

N.A.

Bioaccumulative potential

Component	Bioaccumulation	Test	Duration	Value
4-nonylphenol, branched; Isononylphenol	Not bioaccumulative	BCF - Bioconcentration factor	28 d	740

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN1993

ADR-UN number: 1993

IATA-Un number: 1993

IMDG-Un number: 1993

UN proper shipping name

DOT-Proper Shipping Name: Flammable liquids, n.o.s. (ethylacetate)

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (ethylacetate)

IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (ethylacetate)

IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (ethylacetate)

Transport hazard class(es)

DOT-Hazard Class: 3

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group

DOT Packing Group: III

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

Marine pollutant: No
Environmental Pollutant: Not Applicable
DOT-RQ: Yes DOT-RQ - Quantity: 5000 lbs

Transport in bulk according to IMO instruments

N.A.
Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): B1, B52, IB3, T4, TP1, TP29
DOT-Label(s): 3
DOT-Symbol: N/A
DOT-Cargo Aircraft: 220 L
DOT-Passenger Aircraft: 60 L
DOT-Bulk: 242
DOT-Non-Bulk: 203
DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID) :

ADR-Label: 3
ADR-Hazard identification number: 30
ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA) :

IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisioning: A3

Sea (IMDG) :

IMDG-Stowage and handling: Category A
IMDG-Segregation: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisioning: 223 274 955
IMDG-EMS: F-E, [S-E]

15. REGULATORY INFORMATION

This Safety Data Sheet has been prepared according to the Hazard Communication Standard 2024 (HCS 2024)

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

bis-[4-(2,3-epoxipropoxy)phenyl]propane	is listed in TSCA	Section 8b
ethylacetate; acetic acid ethyl ester	is listed in TSCA	Section 8b
silica sand; quartz	is listed in TSCA	Section 8b
4-nonylphenol, branched; Isononylphenol	is listed in TSCA	Section 8b Section 8a - PAIR Section 5a - SNUR Section 12b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

ethylacetate; acetic acid ethyl ester

Section 313 - Toxic chemical list:

4-nonylphenol, branched; Isononylphenol

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

ethylacetate; acetic acid ethyl ester	Reportable quantity:	5000	pounds
---------------------------------------	----------------------	------	--------

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act**CWA listed substances:**

No substances listed

USA - State specific regulations**California Proposition 65****Substance(s) listed under California Proposition 65:**

silica sand; quartz Listed as carcinogen

Massachusetts Right to know**Substance(s) listed under Massachusetts Right to know:**

ethylacetate; acetic acid ethyl ester

silica sand; quartz

Pennsylvania Right to know**Substance(s) listed under Pennsylvania Right to know:**

ethylacetate; acetic acid ethyl ester

silica sand; quartz

New Jersey Right to know**Substance(s) listed under New Jersey Right to know:**

ethylacetate; acetic acid ethyl ester

silica sand; quartz

Canada - Federal regulations**DSL - Domestic Substances List**

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory**NPRI (National Pollutant Release Inventory) - List of substances listed.**

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 9/24/2025 - version 16

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.7/2	Repr. 2	Reproductive toxicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
B.6/2	Flam. Liq. 2	Flammable Liquids — Category 2
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2
US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 IMDG: International Maritime Code for Dangerous Goods.
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 CLP: Classification, Labeling, Packaging.
 EU CLP Index: Index number as reported in Annex VI to EU Reg. 1272/2008
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 INCI: International Nomenclature of Cosmetic Ingredients.
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 DNEL: Derived No Effect Level.
 PNEC: Predicted No Effect Concentration.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 WGK: German Water Hazard Class.
 KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 16. OTHER INFORMATION