

Safety Data Sheet

ULTRACOAT EASY 60 NA

Safety Data Sheet dated: 09/24/2025 - version 5

Date of first edition: 12/11/2020



1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: ULTRACOAT EASY 60 NA

Trade code: 9073699

Recommended use of the chemical and restrictions on use

Recommended use: Coating

Restrictions on use: Not available

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Skin Sensitization, Category 1

May cause an allergic skin reaction.

Label elements

Hazard pictograms and Signal Word



Warning

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

Hazards associated with foreseeable chemical reactions

None

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥5 - <10 %	2-butoxyethanol; ethylene glycol monobutyl ether	CAS:111-76-2 EC:203-905-0 EU CLP Index:603-014-00-0	Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319
≥0.5 - <0.6 %	ethylene glycol; ethane-1,2-diol	CAS:107-21-1 EC:203-473-3 EU CLP Index:603-027-00-1	Acute Tox. 4, H302; STOT RE 2, H373
≥0.3 - <0.5 %	2,4,7,9-tetramethyl-5-decyne-4,7-diol; Tetramethyl decyne diol	CAS:126-86-3 EC:204-809-1	Eye Dam. 1, H318; Aquatic Chronic 3, H412; Aquatic Acute 3, H402; Skin Sens. 1, H317

The actual concentration of the components listed above is withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

- Wash immediately with water.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Not available

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

- (see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO₂).

Unsuitable extinguishing media:

- None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: Not available
- Explosive properties: Not Relevant
- Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove persons to safety.
- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Data not available.
Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
2-butoxyethanol; ethylene glycol monobutyl ether CAS: 111-76-2	MAK	GERMANY	Long Term: 49 mg/m3 - 10 ppm
	OSHA		Long Term: 240 mg/m3 - 50 ppm prevent or reduce skin absorption;
	ACGIH		Long Term: 20 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;eye and upper respiratory tract irritation;
	MAK	AUSTRIA	Long Term: 98 mg/m3 - 20 ppm; Short Term: 200 mg/m3 - 40 ppm
	MAK	SWITZERLAND	Long Term: 49 mg/m3 - 10 ppm
	OSHA		Long Term: 240 mg/m3 - 50 ppm prevent or reduce skin absorption
	ACGIH		Long Term: 20 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;eye and upper respiratory tract irritation
ethylene glycol; ethane-1,2-diol CAS: 107-21-1	EU		Long Term: 98 mg/m3 - 20 ppm; Short Term: 246 mg/m3 - 50 ppm Skin
	ACGIH		Short Term: Ceiling - 100 mg/m3 (H), A4 - URT and eye irr
	MAK	GERMANY	Long Term: 26 mg/m3 - 10 ppm
	ACGIH		Long Term: 25 ppm; Short Term: 10 mg/m3 - 50 ppm A4 - Not Classifiable as a Human Carcinogen;upper respiratory tract irritation
	MAK	AUSTRIA	Long Term: 26 mg/m3 - 10 ppm; Short Term: 52 mg/m3 - 20 ppm
	MAK	SWITZERLAND	Long Term: 26 mg/m3 - 10 ppm
	EU		Long Term: 52 mg/m3 - 20 ppm; Short Term: 104 mg/m3 - 40 ppm Skin

Biological limit values

2-butoxyethanol; Biological Indicator: butoxyacetic acid (BAA); Sampling Period: End of turn
ethylene glycol monobutyl ether Value: 200 MGGCREAT; Medium: Urine
CAS: 111-76-2

Predicted No Effect Concentration (PNEC) values

ethylene glycol; ethane-1,2-diol Exposure Route: Fresh Water; PNEC Limit: 10 mg/l

CAS: 107-21-1

Exposure Route: Marine water; PNEC Limit: 1 mg/l

Exposure Route: Soil; PNEC Limit: 1,53 mg/kg

Exposure Route: Freshwater sediments; PNEC Limit: 37 mg/kg

Exposure Route: Intermittent release; PNEC Limit: 10 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 199,5 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 3,7 mg/kg

Derived No Effect Level (DNEL) values

ethylene glycol; ethane-1,2-diol Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 106 mg/kg; Consumer: 53 mg/kg

CAS: 107-21-1

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 53 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 35 mg/m³; Consumer: 7 mg/m³

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA 294.4 for information on selection and use of appropriate respiratory protection equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and colour:	liquid transparent/white
Odour:	Not Relevant
Odour threshold:	Not Relevant
Melting point / freezing point:	Not Relevant
Initial boiling point and boiling range:	Not Relevant
Flammability:	Not Relevant
Upper/lower flammability or explosive limits:	Not Relevant
Flash point:	100 °C (212 °F)
Auto-ignition temperature:	Not Relevant
Decomposition temperature:	Not Relevant

pH:	Not Relevant
Viscosity:	Not Relevant
Kinematic viscosity:	No data available
Solubility in water:	very soluble
Solubility in oil:	insoluble
Partition coefficient (n-octanol/water):	Not Relevant
Vapour pressure:	Not Relevant
Evaporation rate:	Not Relevant
Relative density:	1.80 g/cm ³
Vapour density:	Not Relevant

Particle characteristics:

Particle size:	No data available
----------------	-------------------

Other information

Explosive properties:	Not Relevant
Oxidizing properties:	Not Relevant
Solid/gas flammability:	Not Relevant
Substance Groups relevant properties:	Not Relevant
Miscibility:	Not Relevant
Fat Solubility:	Not Relevant
Conductivity:	Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

No data available

Incompatible materials

Data not available.

Hazardous decomposition products

Data not available.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified

	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

2-butoxyethanol; ethylene glycol monobutyl ether a) acute toxicity LD50 Oral Guinea pig = 1414, mg/kg

ethylene glycol; ethane-1,2-diol a) acute toxicity LC50 Inhalation Rat > 2,5 mg/l 6h
LD50 Skin Mouse > 3500, mg/kg bw

2,4,7,9-tetramethyl-5-decyne-4,7-diol; Tetramethyl decyne diol a) acute toxicity LD50 Skin Rabbit > 1000 mg/kg
LC50 Inhalation Rat > 20 mg/l 1h

Substance(s) listed on the IARC Monographs:

2-butoxyethanol; ethylene glycol monobutyl ether Group 3

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
2-butoxyethanol; ethylene glycol monobutyl ether	CAS: 111-76-2 - EINECS: 203-905-0 - INDEX: 603-014-00-0	a) Aquatic acute toxicity : LC50 Fish <i>Lepomis macrochirus</i> = 1490 mg/L 96h EPA a) Aquatic acute toxicity : EC50 <i>Daphnia magna</i> > 1000 mg/L 48h EPA a) Aquatic acute toxicity : LC50 Fish <i>Lepomis macrochirus</i> = 2950 mg/L 96h IUCLID
ethylene glycol; ethane-1,2-diol	CAS: 107-21-1 - EINECS: 203-473-3 - INDEX: 603-027-00-1	a) Aquatic acute toxicity : EC50 <i>Daphnia</i> > 100 mg/L 48h

- a) Aquatic acute toxicity : EC50 Algae > 100 mg/L 96
- a) Aquatic acute toxicity : LC50 Fish > 100 mg/L 96
- b) Aquatic chronic toxicity : NOEC Fish > 100 mg/L - 7 d
- b) Aquatic chronic toxicity : NOEC Daphnia > 100 mg/L - 7 d
- b) Aquatic chronic toxicity : NOEC Algae > 100 mg/L 72
- a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 41000 mg/L 96h IUCLID
- a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 14 mL/L 96h EPA
- a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 27540 mg/L 96h EPA
- a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 40761 mg/L 96h IUCLID
- a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 40000 mg/L 96h EPA
- a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 16000 mg/L 96h IUCLID
- a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 46300 mg/L 48h IUCLID
- a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 6500 mg/L 96h IUCLID

2,4,7,9-tetramethyl-5-decyne-4,7-diol; Tetramethyl decyne diol CAS: 126-86-3 - a) Aquatic acute toxicity : LC50 Fish = 42 mg/L
EINECS: 204-809-1

- a) Aquatic acute toxicity : EC50 Daphnia = 91 mg/L
- a) Aquatic acute toxicity : EC50 Algae = 82 mg/L

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

ethylene glycol; ethane-1,2-diol

Reportable quantity:

5000

pounds

CAA - Clean Air Act**CAA listed substances:**

2-butoxyethanol; ethylene glycol monobutyl ether is listed in CAA Section 112(b) - HON Section 112(b) - HAP

ethylene glycol; ethane-1,2-diol is listed in CAA Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act**CWA listed substances:**

No substances listed

USA - State specific regulations**California Proposition 65****Substance(s) listed under California Proposition 65:**

ethylene glycol; ethane-1,2-diol Listed as reproductive toxicant

Massachusetts Right to know**Substance(s) listed under Massachusetts Right to know:**

2-butoxyethanol; ethylene glycol monobutyl ether

ethylene glycol; ethane-1,2-diol

Pennsylvania Right to know**Substance(s) listed under Pennsylvania Right to know:**

2-butoxyethanol; ethylene glycol monobutyl ether

ethylene glycol; ethane-1,2-diol

New Jersey Right to know**Substance(s) listed under New Jersey Right to know:**

2-butoxyethanol; ethylene glycol monobutyl ether

ethylene glycol; ethane-1,2-diol

Canada - Federal regulations**DSL - Domestic Substances List**

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory**NPRI (National Pollutant Release Inventory) - List of substances listed.**

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 9/24/2025 - version 5

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
------	----------------------------------	-------------

A.1/3/Inhal	Acute Tox. 3	Acute toxicity (inhalation), Category 3
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2
US-HAE/A3	Aquatic Acute 3	Acute aquatic hazard, category 3
US-HAE/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 IMDG: International Maritime Code for Dangerous Goods.
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 CLP: Classification, Labeling, Packaging.
 EU CLP Index: Index number as reported in Annex VI to EU Reg. 1272/2008
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 INCI: International Nomenclature of Cosmetic Ingredients.
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 DNEL: Derived No Effect Level.
 PNEC: Predicted No Effect Concentration.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 WGK: German Water Hazard Class.
 KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION