

POLY-CRETE URETHANE
FLOORING w/COLOR-FAST
TOPCOAT

POLY-CRETE WR
(MUST BE WET PRIMED w/TF)

MEMBRANE

OPEN WEEP HOLES

FLOOR DRAIN / FLOOR SINK (TYP.)

COMPRESSION FLANGE

PEASTONE TO KEEP WEEP
HOLES CLEAR (1" BERM)

HYDRAULIC CEMENT TO SECURE DRAIN BODY
FULLY GROUTED VOIDS (EXPANSION TYPE
TO IMMOBILIZE FIXTURE)

1-1/2" +/-

DOUBLE CORE

EXISTING SLAB

4 BAND CLAMPS FOR
ALL WET PIPES
(2 BAND CLAMPS NOT ALLOWED)

METAL STUD FRAMING &
DUROCK FORM / BOX

CAULK OR INSULATE TO HOLD
HYDRAULIC CEMENT (FLOWABLE)
(NOTE: A LOOSE FLOWABLE MIX IS REQUIRED)



NOTE: 1st COAT OF MEMBRANE NEEDS TO BE
BETWEEN THE FLANGE

**SHERWIN
WILLIAMS®**

HIGH
PERFORMANCE
FLOORING

sherwin-williams.com/resinflooring
(660) 638-5089

TITLE

POLY-CRETE MD, MDB, MDC, MDQ
DRAIN w/MEMBRANE FOR SUSPENDED SLAB DETAIL

DATE

5/15

SCALE

NTS

DWG NO.

PCMD-24

PROJECT