

CRYLAFLOR™ DECO QUARTZ SL


Crylaflor Deco Quartz SL is a decorative, self-leveling, seamless flooring system consisting of 100% reactive, fast curing, methyl methacrylate (MMA) and colored quartz aggregate. This attractive, industrial floor coating can have a nominal thickness of 3/16"-1/4" and a smooth or slip-resistant surface finish. Colored quartz aggregate is available in fine (5900F) and coarse (5900C) sizes.

BENEFITS

- UV resistant — Ideal for indoor and outdoor use
- Quick cure — Accelerated curing time as fast as 1 hour per coat
- Low-temperature installations — Installs at temperatures as low as 0°F
- Decorative — Multiple blends of pigmented quartz aggregate for a unique look
- Self-leveling — A uniform, more even floor system
- Slip resistant — Textured finishes aid in a safer floor, even when wet

USES


- Stadiums/arenas
- Light manufacturing
- Traffic aisles
- Freezers/coolers
- Grocery stores
- Loading docks
- Pool decks
- Restrooms
- Locker rooms




- | | |
|-----------------------|--------------|
| 0 Primer | 2 Grout Coat |
| 1 Base Coat/Broadcast | 3 Seal Coat |




FEATURED COLORS



Blue Slate



Night Sky



New Granite




Brisket



Brindle




Americano




Lagoon



Autumn Spice




Seascape



Redwood



Mud Pie



Grassland

Unlimited standard and custom blends available. Please see Deco Quartz Color Cards for the extensive collection of standard blends or use our Flooring Visualizer Tool to create your own custom blend at floorvisualizer.sherwin-williams.com. This reproduction approximates the actual color. Factors such as the type of product, degree of gloss, texture, size and shape of the area, lighting, heat or method of application may cause color variance. Contact your Sherwin-Williams representative for details.

ABOUT CHEMICAL RESISTANCE

Sherwin-Williams High Performance Flooring offers a broad range of systems to accommodate nearly every industrial, commercial and institutional setting. Each flooring system includes a standard chemical-resistant topcoat or surface proven to perform under typical conditions.

Important considerations:

- The combination of cleaning solutions, sanitizing chemicals, processing substances and products found in any operational setting is unique.
- Knowing exactly which materials are present — as well as their concentrations and typical exposure times before cleanup — is critical for proper flooring system selection.
- During the specification process, a flooring system's standard chemical-resistant topcoat may get replaced with one better suited to unique facility conditions.

The ability of a flooring system to perform as designed relies heavily on proper selection. Matching each use case with the right chemical-resistant flooring is key to having a facility looking great and functioning at peak level over the long term.

See our Chemical Resistance Guide and other technical resources on our website. Connect with a Sherwin-Williams High Performance Flooring expert for help with specifying an optimal flooring system for your facility.

TYPICAL PHYSICAL PROPERTIES

Percent Reactive	100%
Hardness (Shore D), ASTM D-2240	88-92
Compressive Strength, ASTM C-109	8,300 psi
Tensile Strength, ASTM D-638	2,000 psi
Tensile Strength, ASTM D-307	1,350 psi
Tensile Elongation, ASTM D-638	7.50%
Flexural Strength, ASTM D-790	3,700 psi
Flexural Strength, ASTM C-580	2,700 psi
Flexural Module of Elasticity, ASTM D-790	4.7 x 10 ⁵
Linear Expansion, ASTM D-696	3.5 x 10 ⁻⁵
Bond Strength to Concrete	400 psi substrate fails
Indentation, MIL-D-3134	.025 max
Impact Resistance, MIL-D-3134	Pass
Water Absorption, ASTM D-570	0.04%
Heat Resistance Limitation, Intermittent Continuous	160°F 140°F
Flammability, ASTM D-635	Self-Extinguishing
Abrasion Resistance (CS17 wheel 1000gm load 1000 cycles, ASTM D-4060)	29 mg loss
Static Coefficient of Friction*, ANSI B101.1	> 0.6
Dynamic Coefficient of Friction - Wet*, ANSI A326.3	> 0.42
VOC Content	80-90 g/L

*Sherwin-Williams High Performance Flooring systems can be built to meet or exceed the requirements of Static or Dynamic Coefficient of Friction testing per installation. Contact your Sherwin-Williams territory sales manager or tech representative for more information on alternative textures, grit/grip additives, or smooth coatings for your specific environment. A sample should always be obtained and tested prior to purchase for any non-slip flooring system.

THE SHERWIN-WILLIAMS DIFFERENCE

Sherwin-Williams High Performance Flooring delivers world-class industry subject matter expertise, unparalleled technical and specification service, and unmatched regional commercial team support to our customers around the globe.

United States & Canada

sherwin-williams.com/resin-flooring
swflooring@sherwin.com

©2026 The Sherwin-Williams Company
High Performance Flooring
PM-1530952-08 03/26