

## RESUFLO<sup>™</sup>R SHOP FLOOR<sup>™</sup> MR

Resufloor Shop Floor MR is a seamless, slip-resistant pigmented flooring system with a nominal 1/8" (when using double broadcast method) thickness consisting of 100% solids epoxy and natural quartz aggregates. It is ideal for industrial flooring applications and features a chemical, UV and wear-resistant urethane topcoat.

### BENEFITS

- Heavy duty — Highly abrasion resistant and designed for constant foot/vehicle traffic
- UV stable — Years of service with no ambering or degradation due to UV exposure
- Non-slip — Textured finishes aid in a safer floor, even when wet
- Variable install window — Coat over new or old concrete

### USES

- Mechanical rooms
- Server rooms
- Data centers
- Equipment rooms
- Chiller rooms



## FEATURED COLORS



Canada Gray



Light Gray



Black



Sandy Beige



Rich Green



Regal Blue



Rotunda Red



White



Bright Yellow



Steel Gray



Charcoal



Tile Red

Standard and custom colors available. Please see the Resuflor Standard Industrial Color Card for details or envision a color in your space using our Flooring Visualizer Tool at [floorvisualizer.sherwin-williams.com](http://floorvisualizer.sherwin-williams.com). This reproduction approximates the actual color. Factors such as the type of product, degree of gloss, texture, size and shape of area, lighting, heat or method of application may cause color variance. Contact your Sherwin-Williams representative for details.

## ABOUT CHEMICAL RESISTANCE

Sherwin-Williams High Performance Flooring offers a broad range of systems to accommodate nearly every industrial, commercial and institutional setting. Each flooring system includes a standard chemical-resistant topcoat or surface proven to perform under typical conditions.

### Important considerations:

- The combination of cleaning solutions, sanitizing chemicals, processing substances and products found in any operational setting is unique.
- Knowing exactly which materials are present — as well as their concentrations and typical exposure times before cleanup — is critical for proper flooring system selection.
- During the specification process, a flooring system's standard chemical-resistant topcoat may get replaced with one better suited to unique facility conditions.

The ability of a flooring system to perform as designed relies heavily on proper selection. Matching each use case with the right chemical-resistant flooring is key to having a facility looking great and functioning at peak level over the long term.

See our Chemical Resistance Guide and other technical resources on our website. Connect with a Sherwin-Williams High Performance Flooring expert for help with specifying an optimal flooring system for your facility.

## TYPICAL PHYSICAL PROPERTIES

|                                                     |                          |
|-----------------------------------------------------|--------------------------|
| Tensile Strength, ASTM D-638                        | 4000 psi                 |
| Tensile Strength, ASTM C-307                        | 2,600 psi                |
| Tensile Elongation ASTM D-412                       | 150% (with Resuflor EOC) |
| Indentation/Impact Resistance, MIL D-3134           | Pass/No Cracking         |
| Water Absorption, ASTM D-570                        | 0.04%                    |
| Abrasion Resistance (CS-17 Wheel), ASTM D-4060      | 29 mg loss               |
| Satin Finish with Grit                              | 8 mg loss                |
| Satin Finish with No Grit                           | 12 mg loss               |
| Gloss Finish with Grit                              | 4 mg loss                |
| Gloss Finish with No Grit                           | 10 mg loss               |
| UV Resistance                                       | None/Excellent           |
| Static Coefficient of Friction*, ANSI B101.1        | >0.6                     |
| Dynamic Coefficient of Friction - Wet*, ANSI A326.3 | >0.42                    |

\*Sherwin-Williams High Performance Flooring systems can be built to meet or exceed the requirements of Static or Dynamic Coefficient of Friction testing per installation. Contact your Sherwin-Williams territory sales manager or tech representative for more information on alternative textures, grit/grip additives, or smooth coatings for your specific environment. A sample should always be obtained and tested prior to purchase for any non-slip flooring system.

## THE SHERWIN-WILLIAMS DIFFERENCE

Sherwin-Williams High Performance Flooring delivers world-class industry subject matter expertise, unparalleled technical and specification service, and unmatched regional commercial team support to our customers around the globe.

### United States & Canada

[sherwin-williams.com/resin-flooring](http://sherwin-williams.com/resin-flooring)  
[swflooding@sherwin.com](mailto:swflooding@sherwin.com)

©2026 The Sherwin-Williams Company  
High Performance Flooring  
PM-1530952-08 04/26